

Digital Signage

NEC MULTISYNC ME501



Din vej til digitalisering af skiltning.

- Moderne og slankt design – robust, men elegant, mulighed for diskret integration i hvilken som helst anvendelse og alle miljøer.
- Sikker fjernstyring – styr dine enheder sikkert på afstand ved hjælp af NEC NaviSet Administrator 2. Administrér vedligeholdelsesbehovene proaktivt, og spar tid og ressourcer.
- Brugervenlig betjening og drift – smarte installations-, drifts- og vedligeholdelsesfunktioner sikrer præcise præstationer i hele displayets levetid samt besparelser af tid, anstrengelser og ressource
- Fremtidssikrede forbindelsesmuligheder – udstyret med flere digitale og analoge signalindgange, der opfylder industristandarderne, for at sikre fleksibel integration i AV-infrastrukturer.
- Nem afspilning af indhold - den integrerede USB-medieafspiller understøtter forskellige billedvideofilformater for at sikre nem og alenestående afspilning af indhold.

Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, HDMI Cable, Mounting Bracket, Tabletop Stand, Trolley Stand
Shipping Content	2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual

Panel Technology	VA with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Brightness (cd/m2)	400
Contrast Ratio	8000:1
Response Time (grey to grey avg) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1073 (8bit + FRC)

Shipping Carton Dimensions (W/H/D) mm	1298
Shipping Carton Dimensions (W/H/D) mm	860
Shipping Carton Dimensions (W/H/D) mm	224
Product Weight Without Stand (Kg)	17
Shipping Weight (Kg)	24

DisplayPort	1
HDMI	2
Audio 3.5mm Jack	1

Diagonal Size (inches / cm)	50
Diagonal Size (inches / cm)	126

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Energy Star	True
-------------	------

[AVSpecificationConnectivityOutputAudio35MmJack]1

Special Characteristics	Frame Comp, Powered USB Port (10 W), Removable Logo, Powered USB Port (15 W)
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10 + 10
Power Management	True
Equipment Space (Mounting)	True
Cabinet Colour	Black
Temperature Sensor	True
IP Rating	True
Scheduler / Timer	True
Remote Management	True
Gain Control	True
SNMP	True

Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	85
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	90

Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 400 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6

RS232C IN	1
LAN Port	1
USB	1

Bezel Size (L/R) mm	15
Bezel Size (U) mm	15

Haze Level [%]	1
----------------	---

