

Desktop displays

SHARP / NEC MULTISYNC EX241UN



Ultratynd pynteramme - en målestandard for børserne, der kombinerer et smalt og elegant design med en helbredsbevidst ydeevne.

- Beskyttelse af dine øjne mod træthed og skader - Indbygget lavt blå lys-teknologi bortfiltrerer farlig udledning af blått lys, mens flimmerfri teknologi fjerner enhver flimren i baggrundsbelysningen.
- Højest mulig produktivitet og effektiv multitasking – reducer antallet af PC'er, sammenkæd flere skærme ved hjælp af DisplayPort (udgang), og få glæde af Uniformity Control (styring af ensartethed).
- Effektiv installation og konfiguration – skærmstativ med lynfrigivelse med tryk på én knap, en intuitiv joystick-knap til menuindstillinger og håndtering af et helt miljø med flere skærme.
- Selvjustering af strømforbruget - for at minimere unødvendig brug af strøm justerer de valgfri sensorer for tilstedeværelse af mennesker og omgivende lys (Human and Ambient Light Sensors) skærmens lys
- Fremtidssikret design med flere skærme – den 4-sidede, ultrasmalle pynteramme (der også kan tages af) får skærmene til at fylde så lidt som muligt uden at gå på kompromis med skærmstørrelsen.

Specifikationer

Panel Technology	IPS TFT
Aspect Ratio	16:9
Brightness (cd/m2)	250
Contrast Ratio	1000:1
Display Colours	16.77
Response Time (grey to grey avg) ms	6
Pixel Pitch (mm H/V)	0,2745
Viewing Angle [°]	178
Special Characteristics	ControlSync®, Carbon Savings Meter, DICOM preset, Customize Setting, DDC/CI compatible, RGB Support, Frame Comp, DisplayPort, USB-C, ErgoDesign®, Picture-by-Picture, PLink Support, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, USB ver. 3.0 (3 down / 1 up), USB ver. 3.1 (2 down / 1 up)
Operating Temperature (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Accessories	
Shipping Content	Control Sync Cable, DisplayPort Cable, Monitor, Power Cable, Setup Guide, USB cable
Power Consumption on-mode (IEC62087:2012)	15 (Eco Mode 2), 19 (Eco Mode), 19 (shipping), 45 (max.)
Power Supply	Internal Power Supply
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Product Weight With Stand (Kg)	6
Mounting (VESA/Number of Points/Pitch mm)	100 x 100

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	VESA DDC2B, VESA DDCi
Audio	Headphone Jack, Integrated Speakers (1 W + 1 W)
Adjust Functions	Auto Adjust, Lysstyrke, Kontrast, Control Sync, DV Mode, EcoMode, Fine Adjust (analog), Individual Adjust, Intelligent Power Management, Language Select, LED Brightness, Monitor Information
Safety & Ergonomics	CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, GEEA/Energy Label, ISO 9241-307 (pixel failure class I), Low Blue Light, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight, Optional 1st to 3rd year 24/7 usage warranty, Optional 4th to 5th year warranty extension
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.0 (3 down / 1 up), DVI-D
Analog	D-sub 15 pin
Diagonal Size (inches / cm)	24
Diagonal Size (inches / cm)	60
Colour Gamuts	100 % sRGB, 72% NTSC
Energy Efficiency	ECOMode, Energy consumption: 15 kWh/1000 h, Energy efficiency class: E
Optimum Resolution	1920 x 1080 at 0 Hz
Supported Resolution	1920 x 1080 (60Hz)
Height adjustable stand [mm]	100
Screen Rotate [°]	-90 - 90
Bezel Size (L/R) mm	1

