

Videovæg

PN-V701



The Sharp PN-V701 is truly an original and unique SHARP video wall display mainly designed for video wall applications and multi-screen installations.

- 70" (176.6cm) video wall display with 24/7 Operation
- 1920 x 1080 Pixels with 700cd/m2
- Only 4.4mm bezel between active areas (2.9mm / 1.5mm)
- Contrast 4,000:1
- Advanced UCCT (Colour Uniformity Calibration)
- Mini OPS Module Slot System
- 5 x 5 Multi-screen Capability (Enlargement) internal

Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Operation Manual, Installation Set-Up Manual, CD Rom, Software, Power Cord, Expansion Card, Cable Clamp
Panel Technology	TFT-LCD
Native Resolution (Pixels)	1920 x 1080
Aspect Ratio	16:9
Screen Filter	AG
Backlight Technology	Direct LED
Brightness (cd/m2)	700
Contrast Ratio	4000:1
Display Colours	1064.64
Response Time (grey to grey) ms	6
Pixel Pitch (mm H/V)	0,802
Viewing Angle [°]	178
Active Screen Area (H/V) mm	1538.9 x 865.6
Video Wall Bezel (Content to Content) mm	4
Shipping Carton Dimensions (W/H/D) mm	1865
Shipping Carton Dimensions (W/H/D) mm	1100
Shipping Carton Dimensions (W/H/D) mm	375
Product Weight Without Stand (Kg)	37
Shipping Weight (Kg)	57
DisplayPort	1
DVI-D	1
HDMI	2
Audio 3.5mm Jack	1
VGA	1
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	380
Operating Temperature (oC)	0 - 40
Bezel Size (L/R) mm	3
Bezel Size (U) mm	3
Bezel Size (L) mm	2
Diagonal Size (inches / cm)	70
Diagonal Size (inches / cm)	177
CE, CB Report	True
Energy Efficiency	Energy efficiency class: B

24/7 Operation Certified	True
Limited Manufacturer's Warranty (yrs.)	3
Computer Input - Plug and Play	True
Power Management	True
Option Slot Interface	True
Cabinet Colour	Black
Installation Handles	True
Intelligent Fan	True
Fan Control	Auto, Manual
Temperature Sensor	True
Residual Image Reduction Feature	True
Multi-Screen Function - Videowall Mode (Enlarge Feature)	True
Bezel Correction Feature	True
Multi Language OSD	True
Remote Management	True
Řetězec (Režim Zrcadlo)	True
Adjustment Lock Feature	True
Set Point Copy Feature	True
Power on Delay Feature	True
Displaying Use Time Feature	True
Gain Control	True
Screen Adjustment	True
Colour Temperature Adjustment	True
Gamma Adjustment	True
Self-Adjust	True
Manual Image Size Adjustment	True
Save/Output Logging Feature	True
Hardware Diagnosis	True
Monitor Control Software Support	True
Temperature Control	True
Overscan Setting (AV)	True
RS232C Communication Speed Change	True
IR Pass-through Feature	True
Audio Selection per Image INPUT	True
Sync on Green	True

Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 400
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6

RS232C IN	1
RS232C OUT	1
USB	1

DisplayPort	1
[AVSpecificationConnectivityOutputAudio35MmJack]	1

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

