

Digital Signage

SHARP MULTISYNC P656



Målrettet designet til kontrolrum, passagerinformation og eksklusiv detail- eller virksomhedsskiltning – P6-serien leverer kompromisløs ydeevne, dag efter dag

- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Mission-critical performance – the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.
- Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.

Specifikationer

Panel Technology	IPS with Direct LED backlights
Aspect Ratio	16:9
Brightness (cd/m2)	700
Contrast Ratio	8000:1
Pixel Pitch (mm H/V)	0,372
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Active Screen Area (H/V) mm	1428.48 x 803.52

Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	160
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	80

Bezel Size (L/R) mm	11
Bezel Size (U) mm	11
Bezel Size (L) mm	14

DisplayPort	1
HDMI	2

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Haze Level [%]	Pro 25
----------------	--------

Special Characteristics	DICOM Simulation, CEC Support, HDMI ARC, Scheduler
24/7 Operation Certified	True
Local Dimming	True
Power Management	True
Equipment Space (Mounting)	True
Temperature Sensor	True
Brightness Sensor	True
Residual Image Reduction Feature	True
Scheduler / Timer	True
Remote Management	True
Gain Control	True
SNMP	True

Landscape	True
Portrait	True
Horizontal	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 400 (FDMI)
Mounting Screw Specification (Size/Max Length)	M6

Product Weight Without Stand (Kg)	26
Shipping Weight (Kg)	35

Diagonal Size (inches / cm)	64
Diagonal Size (inches / cm)	163

Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight
--	----------------------------------

