

NEC MultiSync CB751Q



- Out-of-the-box collaboration – thanks to embedded computing with built-in annotation tools and wireless presentation capabilities.
- Protective Glass – premium toughened glass protects the security of the panel yet delivers a perfect touch experience with anti-glare coating to minimise reflections and fingerprints.
- Cost Saving Device Management – save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.
- Multi-Touch – true multi-touch support with up to 20 simultaneous touch points.
- Simple operation – with easy front access to USB ports and controls for major functionalities.

Specificationer

DISPLAY MODULE DATA

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	75 / 189.3
Aspect Ratio	16:9
Backlight Technology	LED
Brightness (cd/m²)	350
Contrast Ratio	1100:1
Response Time (grey to grey avg) ms	8
Viewing Angle (H/V)0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1,073 (10bit)

TOUCH INTERFACE SPECIFICATION

Technology	Infrared Touch
Number of Touch Points	20
Coating / Filter	Anti-glare
Screen Hardness (H)	7
Operating System Compatibility	Native Multi-Touch: Windows 7, Windows 8, Windows 10, Linux, Android; Default Mouse: Windows XP, Windows Vista, Mac OS X
Light Transmission [%]	88 (+/- 1 %)
Haze Level [%]	3
Reflection Rate [%]	4
Touch Method	Finger; Gloves; Stylus (> 8 mm)
Data Interface	USB-HID
Palm Rejection	No
Windows Ink	No

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	17.7
Bezel Size (U/L) mm	17.7 / 45.7
Product Dimensions (W/H/D) mm	1,709.4 x 1,020 x 86.8
Product Weight Without Stand (Kg)	52.6

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	3
VGA	1
Audio 3.5mm Jack	1

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	2
USB	8

KEY SPECIFICATIONS

Special Characteristics	AMX NetLinx Support; HDMI with UHD at 60 Hz; NaViSet Administrator 2; Scheduler
Operating Time	12 / 7
Built in Speakers (W)	2 x 12 W
Cabinet Colour	Black

POWER SUPPLY AND OPERATING ENVIRONMENT

Power Consumption (W) (Operating MAX)	430
Operating Temperature (oC)	+0 to +40
Humidity (%)	10-90

INSTALLATION

Landscape	.
Mounting (VESA/Number of Points/Pitch mm)	4; 800 x 400 (FDMI)

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio/Headphone 3.5mm Jack	1
-----------------------------------	---

ACCESSORIES

Shipping Contents	3 x Stylus; HDMI Cable; Power Cable; Remote Control; USB cable; User Manual; VGA cable; Wall Mount
--------------------------	--



4KUHD

