

NEC MultiSync E658



- Reducerede installations- og driftsomkostninger – et yderst energieffektivt display med LED-baggrundsbelysning sikrer et lavere strømforbrug, baggrundsbelysning med en længere levetid og et lettere de
- Nem afspilning af indhold - den integrerede USB-medieafspiller understøtter forskellige billedvideofilformater for at sikre nem og alenestående afspilning af indhold.
- Alenestående drift – displayet er designet til enkel, alenestående drift takket være integreret USB-medieafspiller, højttalere og planlægningsfunktion.
- Slankt design og indbyggede højttalere – det æstetiske design ser flot ud og muliggør nem og billig installation.
- Fremtidssikrede forbindelsesmuligheder – udstyret med flere digitale og analoge signalindgange, der opfylder industristandarderne, for at sikre fleksibel integration i AV-infrastrukturer.

Specifikationer

DISPLAY MODULE DATA

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	64.5 / 164
Aspect Ratio	16:9
Brightness (cd/m2)	350
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Pixel Pitch (mm H/V)	0.372
Viewing Angle (H/V)0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Haze Level [%]	1

POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)	100-240 V AC; 50 / 60 Hz
Power Consumption (W) (Operating MAX)	225
Operating Temperature (oC)	0 to 40
Storage Temperature [°C]	-10 to +60
Humidity (%)	10 to 80
Storage Humidity [%]	5 to 85

INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	4; 600 x 400 (FDMI)

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio/Headphone 3.5mm Jack	1
----------------------------	---

ACCESSORIES

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Remote Control Transmitter	Yes
Power Cord	Yes
Mounting Bracket	Optional
Tabletop Stand	Optional

KEY SPECIFICATIONS

Special Characteristics

Ambient Light Sensor; Audio settings with equalizer; CEC Support; Colour temperature mode; Display Browser Control; Energy saving picture mode; HDMI with UHD at 60 Hz; HDR Gamma Support (HLG, PQ); Mac and Windows compatible; NaViSet Administrator 2; Powered USB-Port; Retail picture mode; Scheduler; SNMP Support; USB Media Player

HDR High Dynamic Range

Limited Manufacturer's Warranty (yrs.)

Built in Speakers (W)

Cabinet Colour

Colour Versions

3

10W + 10W

Black

Black Front Bezel, Black Back Cabinet

Temperature Sensor

Brightness Sensor

•

•

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	13
Bezel Size (U/L) mm	14.4
Product Dimensions (W/H/D) mm	1,457.5 x 833.9 x 73
Product Weight Without Stand (Kg)	23.8

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	3
VGA	1
Component	1
Composite	1
Audio 3.5mm Jack	1

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	1

4K UHD

