

Big Pad Interaktive displays

# NEC MULTISYNC M491 PCAP

Fremragende touch-præstationer til krævende miljøer.

- Moderne og rengøringsvenligt design – kant til kant med mulighed for diskret integration i hvilken som helst anvendelse og alle miljøer.
- Enestående touch-præstationer – med op til 20 touch-punkter byder PCAP-teknologien på fremragende touch-respons og anvendelse af penne.
- Uhindret læsbarhed – ingen genspejling fra vinduer eller andre lyskilder betyder, at skiltens indhold eller præsentationen i mødelokalet hele tiden er synlige.
- Missionskritisk, klar til drift 24/7 – valget af industrielle komponenter og omhyggeligt design fokuseret på svære anvendelsesscenarier går hånd i hånd med en imponerende og uafbrudt brugeroplevelse.
- Sikker fjernstyring – styr dine enheder sikkert på afstand ved hjælp af NEC NaviSet Administrator 2. Administrér vedligeholdelsesbehovene proaktivt, og spar tid og ressourcer.

# Specifikationer

## Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, USB Cable, HDMI Cable, Pen, Mounting Bracket, Tabletop Stand, Trolley Stand
Shipping Content	2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual, USB cable
Panel Technology	IPS with Edge LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Screen Filter	AG
Backlight Technology	LED
Brightness (cd/m2)	500
Contrast Ratio	8000:1
Response Time (grey to grey avg) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1076 (10bit)
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	80
Operating Temperature (oC)	0 - 35
Storage Humidity [%]	20
Storage Humidity [%]	80
Shipping Carton Dimensions (W/H/D) mm	1298
Shipping Carton Dimensions (W/H/D) mm	860
Shipping Carton Dimensions (W/H/D) mm	224
Product Weight Without Stand (Kg)	30
Shipping Weight (Kg)	38
RS232C IN	1
LAN Port	1
USB	1
Energy Star	True
Light Sensor Processing	-

Number of Touch Points	20
Safety Glass Thickness (mm)	4,5
Pen Mode / Finger Mode	True
Screen Hardness (H)	6
Operating System Compatibility	Android, Linux, Windows, Raspberry Pi
Light Transmission [%]	85 (+/- 5 %)
Touch Method	Conductive Passive Stylus (≥ 8 mm), Finger
Data Interface [AVSpecificationTechnology]	USB-HID Projected Capacitive Touch (P-CAP)
Special Characteristics	Powered USB Port (10 W), Removable Logo
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10 + 10
Power Management	True
Temperature Sensor	True
IP Rating	True
Scheduler / Timer	True
Remote Management	True
E-Mail Notification	True
Landscape	True
Portrait	True
Horizontal	True
Mounting (VESA/Number of Points/Pitch mm)	300 x 300 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6
DisplayPort	1
HDMI	2
Audio 3.5mm Jack	1
Diagonal Size (inches / cm)	49
Diagonal Size (inches / cm)	123

[AVSpecificationConnectivityOutputAudio35MmJack]1

