

LCD Video wall display

PN-V701

The world's largest LCD video wall display



- 70" (176.6cm) video wall display with 24/7 Operation
- Only 4.4mm bezel between active areas (2.9mm / 1.5mm)
- Advanced UCCT (Colour Uniformity Calibration)
- 5 x 5 Multi-screen Capability (Enlargement) internal
- 1920 x 1080 Pixels with 700cd/m2
- Contrast 4,000:1
- Mini OPS Module Slot System

Specifikationer

DISPLAY MODULE DATA

Panel Technology	TFT-LCD
Native Resolution (Pixels)	1920 x 1080
Diagonal Size (inches / cm)	70 / 176,6
Aspect Ratio	16:9
Backlight Technology	LED, Direct array
Brightness (cd/m2)	700
Contrast Ratio	4000:1
Display Colours	1.06 Billion
Response Time (grey to grey avg) ms	6
Viewing Angle (H/V)0 CR >10	178 / 178

POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)	100-240 / 50-60
Power Consumption (W) (Operating MAX)	380
Operating Temperature (oC)	0-40
Humidity (%)	20-80

INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	4 / 400mm x 400mm

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

DisplayPort	1
Audio/Headphone 3.5mm Jack	1

KEY SPECIFICATIONS

24/7 Operation Certified	•
Computer Input - Plug and Play	•
Power Management	•
Multi-Screen Function - Videowall Mode (Enlarge Feature)	•
Bezel Correction Feature	•
Remote Management	•
Daisychain (Mirror mode)	•
Hardware Diagnosis	•
Monitor Control Software Support	•

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	2.9 / 1.5
Bezel Size (U/L) mm	2.9 / 1.5
Video Wall Bezel (Content to Content) mm	4.4
Product Dimensions (W/H/D) mm	1,543.7 x 870.4 x 122
Product Weight Without Stand (Kg)	37

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	2
DVI-D	1
DisplayPort	1
VGA	1
Audio 3.5mm Jack	1

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
RS232C OUT	1
LAN Port	1
Other	Mini OPS Slot