

Digital Signage

# SHARP MULTISYNC® E509



Sharp MultiSync® E9-serien er indgangsniveauet for professionelle displayløsninger og er udviklet til moderne arbejdsmiljøer, der har behov for mere end det, en almindelig forbruger TV kan tilbyde.

- Optimal læsbarhed – et high haze panel reducerer blænding fra vinduer og omgivende lys, så skiltindhold og præsentationer er tydelige og letlæselige i alle miljøer.
- Standardiseret funktionalitet – deler samme design, betjening og enhedsstyring som øvrige skærme i Sharps displayportefølje, hvilket sikrer en ensartet brugeroplevelse og problemfri fjernstyring.
- Nem plugandplay skiltning – den integrerede USBmedieafspiller gør det muligt at afspille UHD indhold direkte med autostart, så digital skiltning kan startes med det samme uden ekstern hardware eller CMS.
- Fleksibel orientering – designet til både stående og liggende installation, med en ramme der har samme bredde hele vejen rundt for et rent og professionelt udtryk.

# Specifikationer

Bezel Size (L/R) mm	11
Bezel Size (U/L) mm	11
Response Time (grey to grey avg) ms	8
Special Characteristics	USB Media Player, NaViSet Administrator 2, CEC Support, Powered USB-Port, HDMI ARC, Scheduler
Built in Speakers (W)	10 + 10
Remote Management	True
Operating Time	16/7
[AVSpecificationSupportedImageFormats]	Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK)
Optimum Resolution	3840 x 2160 at 60 Hz
Supported Resolution	1920 x 1200, 1024 x 768 , 1280 x 1024, 1920 x 1080, 640 x 480, 1280 x 720, 1280 x 960, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1400 x 1050, 4096 x 2160
Colour Versions	Black Back Cabinet, Black Front Bezel
Safety & Ergonomics	UKCA, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, VCCI, RCM
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight
Shipping Carton Dimensions (W/H/D) mm	1253
Shipping Carton Dimensions (W/H/D) mm	761
Shipping Carton Dimensions (W/H/D) mm	128
Shipping Weight (Kg)	13
Power Consumption on-mode (IEC62087:2012)	99 (shipping)
Power Supply	100-240 V, Internal Power Supply
[AVSpecificationLandscapeDimensionsWidthMm]	1120
[AVSpecificationLandscapeDimensionsHeightMm]	641
[AVSpecificationLandscapeDimensionsDepthMm]	60
Diagonal Size (inches / cm)	50
Diagonal Size (inches / cm)	126
Digital Output Control	HDMI, USB Type C LAN 100Mbit
[AVSpecificationControlTerminals]	RS232C, LAN

Panel Technology	VA with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Brightness (cd/m2)	350
Contrast Ratio	4000:1
Pixel Pitch (mm H/V)	0,285
Viewing Angle [°]	178
Colour Depth [bn]	1.07 (8bit + FRC)
Active Screen Area (H/V) mm	1095 x 616
Max. screen time	up to 16 hours of use per day
Response Time (typ.) [ms]	8
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Via AC Adapter	True
Operating Voltage(DCV)	100-240
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	80
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
[AVSpecificationBattery]	< 0.5 (ECO Standby)
Portrait	True
Landscape	True
Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	200 x 200 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6
<b>Accessories</b>	
[AVSpecificationAccessories]	[feet], [wall-mount], [usb-c-cable], [trolley]
Shipping Content	Cable Clamps, Power Cable, Remote Control, 2 x AAA batteries, Setup Manual, Display
Energy Efficiency	LED backlight technology, Energy consumption: 90 kWh/1000 h, Energy efficiency class: G
Ecological Standards	Energy Star 8.0
Bezel Size (L/R) mm	11
Bezel Size (U) mm	11
Bezel Size (L) mm	11
RS232C IN	9600
RS232C OUT	9600
Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	24 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Built in Speakers (W)	Internal 10W + 10W
Audio 3.5mm Jack	1
[AVSpecificationWeightKg]	9

Haze Level [%]	Pro 25
[AVSpecificationInputData]	1 x USB 2.0 (MediaPlayer)



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett\_x0002\_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync® E509, 19/5/2026