

Digital Signage

NEC MULTISYNC E498



De funktioner, du har brug for, til den pris, du ønsker.

- Slankt design og indbyggede højttalere – det æstetiske design ser flot ud og muliggør nem og billig installation.
- Fremtidssikrede forbindelsesmuligheder – udstyret med flere digitale og analoge signalindgange, der opfylder industristandarderne, for at sikre fleksibel integration i AV-infrastrukturer.
- Nem afspilning af indhold - den integrerede USB-medieafspiller understøtter forskellige billedvideofilformater for at sikre nem og alenestående afspilning af indhold.
- Professionel integration – med essentiel RS232-funktionalitet, IR- og knaplås og digital lydudgang S/PDIF kan skærmen nemt integreres i applikationer i offentlige miljøer.
- Alenestående drift – displayet er designet til enkel, alenestående drift takket være integreret USB-medieafspiller, højttalere og planlægningsfunktion.

Specifikationer

Accessories

| | |
|------------------------------|--|
| [AVSpecificationAccessories] | Remote Control Transmitter, Installation Set-Up Manual, AC Adapter, Power Cord, HDMI Cable, Mounting Bracket |
| Shipping Content | 2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual |

| | |
|-------------------------------------|--------------------------------|
| Panel Technology | IPS with Direct LED backlights |
| Native Resolution (Pixels) | 3840 x 2160 |
| Aspect Ratio | 16:9 |
| Backlight Technology | Direct LED |
| Brightness (cd/m2) | 350 |
| Contrast Ratio | 1200:1 |
| Response Time (grey to grey avg) ms | 8 |
| Pixel Pitch (mm H/V) | 0,28 |
| Viewing Angle [°] | 178 |
| Colour Depth [bn] | 1073 (10bit) |
| Active Screen Area (H/V) mm | 1073.8 x 604 |

| | |
|---------------------------------------|----------|
| Power Consumption (W) (Operating MAX) | 185 |
| Operating Temperature (oC) | 0 - 40 |
| Storage Temperature [°C] | -10 - 60 |
| Storage Humidity [%] | 5 |
| Storage Humidity [%] | 85 |

| | |
|--|-----------|
| Landscape | True |
| Mounting (VESA/Number of Points/Pitch mm) | 400 x 200 |
| Mounting (VESA/Number of Points/Pitch mm) | 4 |
| Mounting Screw Specification (Size/Max Length) | M6 |

| | |
|-----------------------------|-----|
| Diagonal Size (inches / cm) | 49 |
| Diagonal Size (inches / cm) | 123 |

| | |
|---------------------|----|
| Bezel Size (L/R) mm | 38 |
| Bezel Size (U) mm | 37 |

[AVSpecificationConnectivityOutputAudio35MmJack]1

Special Characteristics

| | |
|--|---------|
| Limited Manufacturer's Warranty (yrs.) | 3 |
| Built in Speakers (W) | 10 + 10 |
| Cabinet Colour | Black |
| Temperature Sensor | True |
| Residual Image Reduction Feature | True |
| Scheduler / Timer | True |
| Gain Control | True |
| SNMP | True |

| | |
|------------------|---|
| Component | 1 |
| Composite | 1 |
| HDMI | 3 |
| Audio 3.5mm Jack | 1 |
| VGA | 1 |

| | |
|---------------------------------------|---|
| Shipping Carton Dimensions (W/H/D) mm | 1 |
| Shipping Carton Dimensions (W/H/D) mm | 1 |
| Shipping Carton Dimensions (W/H/D) mm | 0 |
| Product Weight Without Stand (Kg) | 5 |

| | |
|-----------|---|
| RS232C IN | 1 |
| LAN Port | 1 |
| USB | 1 |

| | |
|------------------------------|----|
| Operating Humidity (min) [%] | 10 |
| Operating Humidity (max) [%] | 80 |

| | |
|----------------|---|
| Haze Level [%] | 1 |
|----------------|---|

