

Digital Signage

# NEC MULTISYNC M551



## Intuitiv, professionel levering af indhold.

- Moderne og slankt design – robust, men elegant, mulighed for diskret integration i hvilken som helst anvendelse og alle miljøer.
- Sikker fjernstyring – styr dine enheder sikkert på afstand ved hjælp af NEC NaviSet Administrator 2. Administrér vedligeholdelsesbehovene proaktivt, og spar tid og ressourcer.
- Uhindret læsbarhed – ingen genspejling fra vinduer eller andre lyskilder betyder, at skiltens indhold eller præsentationen i mødelokalet hele tiden er synlige.
- Missionskritisk, klar til drift 24/7 – valget af industrielle komponenter og omhyggeligt design fokuseret på svære anvendelsesscenerier går hånd i hånd med en imponerende og uafbrudt brugeroplevelse.
- Fremtidssikrede forbindelsesmuligheder – udstyret med flere digitale og analoge signalindgange, der opfylder industristandarderne, for at sikre fleksibel integration i AV-infrastrukturer.

# Specifikationer

## Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, HDMI Cable, Mounting Bracket, Tabletop Stand, Trolley Stand
Shipping Content	2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual

Panel Technology	IPS with Edge LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Backlight Technology	Edge LED
Brightness (cd/m2)	500
Contrast Ratio	8000:1
Response Time (grey to grey avg) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1076 (10bit)

Shipping Carton Dimensions (W/H/D) mm	1430
Shipping Carton Dimensions (W/H/D) mm	920
Shipping Carton Dimensions (W/H/D) mm	250
Product Weight Without Stand (Kg)	26
Shipping Weight (Kg)	37

DisplayPort	1
HDMI	2
Audio 3.5mm Jack	1

RS232C IN	1
LAN Port	1
USB	1

Diagonal Size (inches / cm)	55
Diagonal Size (inches / cm)	139

Energy Star	True
-------------	------

[AVSpecificationConnectivityOutputAudio35MmJack]1

Special Characteristics	Frame Comp, Powered USB Port (10 W), Removable Logo, Powered USB Port (15 W)
Limited Manufacturer's Warranty (yrs.)	3
Local Dimming	True
Built in Speakers (W)	10 + 10
Power Management	True
Equipment Space (Mounting)	True
Cabinet Colour	Black
Temperature Sensor	True
Brightness Sensor	True
Residual Image Reduction Feature	True
IP Rating	True
Scheduler / Timer	True
Remote Management	True
Gain Control	True
SNMP	True

Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	110
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	90

Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	300 x 300 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6

Bezel Size (L/R) mm	13
Bezel Size (U) mm	12
Bezel Size (L) mm	16

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Haze Level [%]	28
----------------	----

