

Desktop displays

SHARP/ NEC MULTISYNC E274FL



For at reducere omkostningerne uden at gå på kompromis med kvaliteten, prioriterer E-serien brugerkomfort og produktivitet, hvilket gør den til en fremragende løsning til både hjemmekontoret og for små og mellemstore virksomheder.

- Forbedre din produktivitet – med indbygget LAN og USB-C fungerer denne skærm som en docking-hub i dit personlige arbejdsområde.
- Fremtidssikret fleksibilitet – bred tilslutning giver fleksibilitet på højt niveau med LAN, DP, HDMI, USB Type C, USB A og lydoutput.
- Sikring af brugernes velvære – indbygget Low Blue Light-teknologi filtrerer farlige blå lys ud, mens Flicker-Free-teknologi eliminerer enhver baggrundslysflimmer.
- Ergonomisk kontor – fuld højdejusterbarhed (130 mm), dreje-, vippe- og drejningsfunktionalitet sikrer perfekt individuel arbejdsopstilling.
- Bedst i form og funktion – fremtidsklart design med 3-sidet ultrasmal kant, tilgængelig i sort eller hvid, plus valgfri VESA-monteringsplade til tynde klientenheder.

Specifikationer

Panel Technology	VA TFT with W-LED backlight
Aspect Ratio	16:9
Brightness (cd/m2)	250
Contrast Ratio	1000:1
Display Colours	16.77
Response Time (grey to grey avg) ms	6
Pixel Pitch (mm H/V)	0,275
Viewing Angle [°]	178
Height adjustable stand [mm]	120
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	610
[AVSpecificationLandscapeDimensionsDepthMm]	283
[AVSpecificationLandscapeDimensionsHeightMinMm]	377
[AVSpecificationLandscapeDimensionsHeightMaxMm]	507
Digital	DisplayPort, HDMI, USB Type C (60 W), USB ver. 3.1 (3 down / 1 up)
Output Control	1 x RJ45
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	RoHS compliant, TCO 9.0
Mounting (VESA/Number of Points/Pitch mm)	100 x 100
Kensington Lock	True
Diagonal Size (inches / cm)	27
Diagonal Size (inches / cm)	69
Power Consumption on-mode (IEC62087:2012)	14 (Eco Mode 2), 20 (typ.)
Power Supply	Integrated Power Supply
Special Characteristics	Low Blue Light, Local dimming

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable), Headphone Jack
Safety & Ergonomics	EnergyStar 8.0, Flicker-free, Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight
Operating Temperature (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Bezel Size (L/R) mm	1
Bezel Size (U) mm	16
Bezel Size (L) mm	16
Product Weight Without Stand (Kg)	5
Product Weight With Stand (Kg)	8
Accessories	
Shipping Content	DisplayPort Cable, Power Cable, Setup Guide, USB-C Cable
Horizontal Frequency [kHz]	31.5 - 81
Vertical Frequency [Hz]	50 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Optimum Resolution	1920 x 1080 at 60 Hz

