

Desktop displays

SHARP / NEC MULTISYNC EA271Q



Fremtidssikret, professionel kontorproduktivitet, der kombinerer visning i topklasse med fremragende ergonomi.

- Der kan ses flere detaljer på skærmen - Quad HD-opløsningen på op til 2560 x 1440 pixel giver 1,75 gange flere skærmdetaljer end fuld HD.
- Den nyeste tilslutningsstandard USB af type C - optimér tilslutningerne, og hold orden på dit skrivebord: Erstat video-, lyd-, strøm- og USB-kablerne med blot ét kabel.
- Maksimalt fokus på helbred og velvære – med en enestående, ergonomisk højdejustering fra 0 til 150 mm, indbygget lavt blåt lys og flimmerfri teknologi plus indbygget omgivende lyssensor.
- Nem styring af flere skærme - håndterer indstillingerne af op til 8 skærme i en konfiguration med flere skærme via hovedskærmen med ControlSync® teknologi.
- Bedst i form og funktion - et fremtidsklart design med 3-sidet, ultrasmal pynteramme, der kan fås i sort eller hvid og matcher kontorets friske, professionelle indretning.

Specifikationer

Panel Technology	IPS TFT with W-LED backlight
Aspect Ratio	16:9
Brightness (cd/m2)	350
Contrast Ratio	1000:1
[AVSpecificationDynamicContrastRatio]	7000:1
Display Colours	16.78
Response Time (grey to grey avg) ms	6
Pixel Pitch (mm H/V)	0,233
Viewing Angle [°]	178
Height adjustable stand [mm]	150
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	362
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	629
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
Energy Efficiency	Ambient light sensor, ECOMode, Energy consumption: 21 kWh/1000 h, Energy efficiency class: E, Human sensor
Ecological Standards Ecological Materials	Minimal use of harmful material Energy Star 8.0, ErP compliant, RoHS compliant, TCO 8.0, [tco-edge]
Optimum Resolution	2560 x 1440 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1152 x 864, 1600 x 1200, 1920 x 1080, 1920 x 1440, 2560 x 1440, 640 x 480, 800 x 600, 832 x 624
Operating Temperature (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Accessories	
Shipping Content	Control Sync Cable, DisplayPort Cable, Monitor, Power Cable, Setup Guide, USB cable
Mounting (VESA/Number of Points/Pitch mm)	100 x 100
Kensington Lock	True
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Product Weight With Stand (Kg)	9

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	DDC2B/2Bi, EDID Standard, VESA DDC/CI
Audio	1W + 1W (De-activateable), Headphone Jack
Adjust Functions	Audio Volume / Lock-Out, Auto Adjust, Lysstyrke, Colour Temperature Control, Kontrast, Control Sync, DV Mode, EcoMode, Human Sensing, Intelligent Power Management, Language Select, Monitor Information, On- Screen-Display (OSD) lock-out, One Touch Recovery, Power-Off Timer
Safety & Ergonomics	CE, EAC, ErP, Flicker-free, ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TCO 8.0, TCO Edge Certified 1.2; TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight, Optional 1st to 3rd year 24/7 usage warranty, Optional 4th to 5th year warranty extension
Special Characteristics	DDC/CI compatible, RGB Support, Frame Comp, PLink Support, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Touch Sensor Keys, USB ver. 3.0 (3 down / 1 up), Flicker Free
Power Consumption on-mode (IEC62087:2012)	150 (max.), 30 (Eco Mode 2), 37 (Eco Mode 1), 37 (shipping), 37 (typ.)
Power Supply	0.75 A/1.6 A, 100-240 V, Internal Power Supply
Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.1 (3 down / 1 up), USB Type C (60 W), DVI-D (Dual Link)
Diagonal Size (inches / cm)	27
Diagonal Size (inches / cm)	68
Colour Gamuts	100 % sRGB, 75 % NTSC
Horizontal Frequency [kHz]	31.5 - 94
Vertical Frequency [Hz]	50 - 75
Bezel Size (L/R) mm	1
Bezel Size (U) mm	1

