

Digital Signage

# NEC MULTISYNC P754Q



## Definitionen af digital skiltning.

- Fremragende læsbarhed – afspilning af indhold takket være høj lysstyrke på 650 cd/m<sup>2</sup> og anti-reflekterende skærmoverflade, selv under varierende og krævende omgivelserforhold.
- Missionskritisk 24/7 klar drift – valget af komponenter i industriel kvalitet og omhyggeligt design fokuseret på krævende brugsscenarier ledsager en imponerende og kontinuerlig seeroplevelse.
- Fremtidsklar med Open Modular Intelligence Expansion – opgrader din skærms kraft ved at integrere en af NECs muligheder for OPS Slot-in pc'er, Raspberry Pi computermodule eller signalgrænseflader.
- Fremtidssikret signaltilslutning og -behandling – adskillige native UHD-opløsningsindgange med 60Hz opdateringshastighed plus automatisk opskalering til UHD for andre signaler giver pixelfri visning
- Forbedret billedbehandling – avancerede indstillinger af relevante visuelle parametre giver fuld kontrol over lysstyrke, farve, gamma og ensartethed via SpectraView Engine for præcise, naturlige bill

# Specifikationer

## Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, CD Rom, AC Adapter, Power Cord, Brightness Sensor, USB Cable, DisplayPort Cable, Mounting Bracket, Tabletop Stand, Trolley Stand
Shipping Content	Display, DisplayPort Cable, Remote Control, USB cable, CD-ROM (User Guides/Manuals)

Panel Technology	IPS with Edge LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Brightness (cd/m2)	650
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Active Screen Area (H/V) mm	698 x 39

Shipping Carton Dimensions (W/H/D) mm	1830
Shipping Carton Dimensions (W/H/D) mm	1190
Shipping Carton Dimensions (W/H/D) mm	280
Product Weight Without Stand (Kg)	53
Shipping Weight (Kg)	66

RS232C IN	1
LAN Port	1
USB	4

Diagonal Size (inches / cm)	75
Diagonal Size (inches / cm)	189

Bezel Size (L/R) mm	15
Bezel Size (U) mm	15

Energy Star	True
-------------	------

24/7 Operation Certified	True
Limited Manufacturer's Warranty (yrs.)	3
Local Dimming	True
Built in Speakers (W)	10 + 10
Power Management	True
Option Slot Interface	True
Equipment Space (Mounting)	True
Cabinet Colour	Black
Temperature Sensor	True
Brightness Sensor	True
IP Rating	True
Scheduler / Timer	True
Gain Control	True
SNMP	True

Landscape	True
Portrait	True
Horizontal	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 400 (FDMI), 600 x 400 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M8

DisplayPort	2
HDMI	3
Audio 3.5mm Jack	1

Power Consumption (W) (Operating MAX)	250
Operating Temperature (oC)	0 - 40

DisplayPort	1
[AVSpecificationConnectivityOutputAudio35MmJack]1	

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Colour Versions	Optional Coloured Overframes
-----------------	------------------------------

Haze Level [%]	28
----------------	----

