

Desktop displays

SHARP/ NEC MULTISYNC E244FL



For at reducere omkostningerne uden at gå på kompromis med kvaliteten, prioriterer E-serien brugerkomfort og produktivitet, hvilket gør den til en fremragende løsning til både hjemmekontoret og for små og mellemstore virksomheder.

- Forbedre din produktivitet – med indbygget LAN og USB-C fungerer denne skærm som en docking-hub i dit personlige arbejdsområde.
- Fremtidssikret fleksibilitet – bred tilslutning giver fleksibilitet på højt niveau med LAN, DP, HDMI, USB Type C, USB A og lydoutput.
- Sikring af brugernes velvære – indbygget Low Blue Light-teknologi filtrerer farlige blå lys ud, mens Flicker-Free-teknologi eliminerer enhver baggrundslysflimmer.
- Ergonomisk kontor – fuld højdejusterbarhed (130 mm), dreje-, vippe- og drejningsfunktionalitet sikrer perfekt individuel arbejdsopstilling.
- Bedst i form og funktion – fremtidsklart design med 3-sidet ultrasmal kant, tilgængelig i sort eller hvid, plus valgfri VESA-monteringsplade til tynde klientenheder.

Specifikationer

Panel Technology	VA TFT with W-LED backlight
Aspect Ratio	16:9
Brightness (cd/m2)	250
Contrast Ratio	1000:1
Display Colours	16.77
Response Time (grey to grey avg) ms	6
Pixel Pitch (mm H/V)	0,275
Viewing Angle [°]	178
<hr/>	
Height adjustable stand [mm]	120
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	610
[AVSpecificationLandscapeDimensionsDepthMm]	283
[AVSpecificationLandscapeDimensionsHeightMinMm]	377
[AVSpecificationLandscapeDimensionsHeightMaxMm]	507
<hr/>	
Digital	DisplayPort, HDMI, USB Type C (60 W), USB ver. 3.1 (3 down / 1 up)
Output Control	1 x RJ45
<hr/>	
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	RoHS compliant, TCO 9.0
<hr/>	
Mounting (VESA/Number of Points/Pitch mm)	100 x 100
Kensington Lock	True
<hr/>	
Diagonal Size (inches / cm)	24
Diagonal Size (inches / cm)	60
<hr/>	
Power Consumption on-mode (IEC62087:2012)	13 (Eco Mode 2), 19 (typ.)
Power Supply	Integrated Power Supply
<hr/>	
Special Characteristics	Low Blue Light, Local dimming

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable), Headphone Jack
Safety & Ergonomics	EnergyStar 8.0, Flicker-free, Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight

Operating Temperature (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85

Bezel Size (L/R) mm	1
Bezel Size (U) mm	16
Bezel Size (L) mm	16

Product Weight Without Stand (Kg)	5
Product Weight With Stand (Kg)	8

Accessories

Shipping Content	DisplayPort Cable, Power Cable, Setup Guide, USB-C Cable
------------------	--

Horizontal Frequency [kHz]	31.5 - 81
Vertical Frequency [Hz]	50 - 75

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Optimum Resolution	1920 x 1080 at 60 Hz
--------------------	----------------------

