



Big Pad Interaktive displays

SHARP/ NEC MULTISYNC ME501 IR-2

ME-serien er designet til lokale detailhandlere, restauranter og små virksomheder og sikrer en pålidelig ydeevne til en overkommelig pris.

- Moderne og slankt design – robust, men elegant, hvilket giver mulighed for diskret integration i enhver applikation og miljø.
- Inspirerende berøringsydelse øger brugeroplevelsen – den hurtige, stabile og robuste berøringsydelse understøtter op til 20 berøringspunkter.
- Elastisk og holdbar – termisk hærdet glas med anti-refleksbelægning modstår hærværk og sikrer perfekt læsbarhed med reduceret refleksion og minimal synlighed af fingeraftryk.
- Future Ready Connectivity – med flere industristandard digitale og analoge signalindgange til fleksibel integration i AV-infrastrukturer.
- Sikker fjernstyring – fjernstyr dine enheder på en sikker måde ved hjælp af NEC NaviSet Administrator 2; administrere vedligeholdelseskrav proaktivt, hvilket sparer tid og ressourcer

Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, USB Cable, HDMI Cable, Mounting Bracket, Trolley Stand, Battery
Shipping Content	2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual, USB cable
Panel Technology	VA with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Screen Filter	AG
Backlight Technology	LED
Brightness (cd/m2)	400
Contrast Ratio	8000:1
Response Time (grey to grey avg) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1073 (8bit + FRC)
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	85
Operating Temperature (oC)	0 - 35
Storage Humidity [%]	20
Storage Humidity [%]	80
Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 400 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6
Diagonal Size (inches / cm)	50
Diagonal Size (inches / cm)	126
Bezel Size (L/R) mm	25
Bezel Size (U) mm	25
Light Sensor Processing	-

Special Characteristics	Powered USB Port (10 W), Removable Logo
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10 + 10
Power Management	True
Temperature Sensor	True
Scheduler / Timer	True
Remote Management	True
E-Mail Notification	True
SNMP	True
Operating Time	18/7

Number of Touch Points	20
Pen Mode / Finger Mode	True
Screen Hardness (H)	7
Operating System Compatibility	Android, Linux, Windows, Raspberry Pi, Mac OSX
Thickness [mm]	3
Light Transmission [%]	92 (+/- 2 %)
Data Interface	USB-HID
Accuracy [mm]	1
[AVSpecificationTechnology]	Infrared

Shipping Carton Dimensions (W/H/D) mm	1298
Shipping Carton Dimensions (W/H/D) mm	860
Shipping Carton Dimensions (W/H/D) mm	224
Product Weight Without Stand (Kg)	27
Shipping Weight (Kg)	34

DisplayPort	1
HDMI	2
Audio 3.5mm Jack	1
RS232C IN	1
LAN Port	1
USB	1

Energy Star	True
-------------	------

[AVSpecificationConnectivityOutputAudio35MmJack]1

