

NEC MultiSync P754Q



- Fremragende læsbarhed – afspilning af indhold takket være høj lysstyrke på 650 cd/m² og anti-reflekerende skærmoverflade, selv under varierende og krævende omgivelsesforhold.
- Fremtidsklar med Open Modular Intelligence Expansion – opgrader din skærms kraft ved at integrere en af NECs muligheder for OPS Slot-in pc'er, Raspberry Pi computermøduler eller signalgrænseflader.
- Forbedret billedbehandling – avancerede indstillinger af relevante visuelle parametre giver fuld kontrol over lysstyrke, farve, gamma og ensartethed via SpectraView Engine for præcise, naturlige billeder
- Missionskritisk 24/7 klar drift – valget af komponenter i industriel kvalitet og omhyggeligt design fokuseret på krævende brugsscenarier ledsager en imponerende og kontinuerlig seeroplevelse.
- Fremtidssikret signaltilslutning og -behandling – adskillige native UHD-opløsningsindgange med 60Hz opdateringshastighed plus automatisk opskalering til UHD for andre signaler giver "pixelfri visning

Specifikationer

DISPLAY MODULE DATA

Panel Technology	IPS with Edge LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	75 / 189
Aspect Ratio	16:9
Brightness (cd/m ²)	650, 450 (shipment setting)
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Viewing Angle (H/V) @ CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (10bit)
Haze Level [%]	28

POWER SUPPLY AND OPERATING ENVIRONMENT

Power Consumption (W) (Operating MAX)	250
Operating Temperature (°C)	0 to 40
Humidity (%)	20 to 80

INSTALLATION

Landscape	•
Portrait	•
Horizontal	•
Mounting (VESA/Number of Points/Pitch mm)	4; 400 x 400 (FDMI); 600 x 400 (FDMI)

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

DisplayPort	1
Audio/Headphone 3.5mm Jack	1

ACCESSORIES

Shipping Content	CD-ROM (User Guides / Manuals); Display; DisplayPort Cable; Remote Control; USB cable
Remote Control Transmitter	Yes
Power Cord	Yes
Mounting Bracket	Optional
Tabletop Stand	Optional

KEY SPECIFICATIONS

24/7 Operation Certified	•
Limited Manufacturer's Warranty (yrs.)	3
Local Dimming	•
Built in Speakers (W)	10 + 10
Power Management	•
Cabinet Colour	Black
Colour Versions	Optional coloured overframes
Temperature Sensor	•
Brightness Sensor	•

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	14.8
Bezel Size (U/L) mm	14.8
Product Dimensions (W/H/D) mm	1,681 x 960 x 71
Shipping Carton Dimensions (W/H/D) mm	1,830 x 1,190 x 280
Product Weight Without Stand (Kg)	53
Shipping Weight (Kg)	65.5

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	3
DisplayPort	2
Audio 3.5mm Jack	1

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	4

