

Digital Signage

SHARP/ NEC MULTISYNC E758



Nyttige funktioner til præsentationer og digital skiltning.

- Reducerede installations- og driftsomkostninger – et yderst energieffektivt display med LED-baggrundsbelysning sikrer et lavere strømforbrug, baggrundsbelysning med en længere levetid og et lettere de
- Slankt design og indbyggede højttalere – det æstetiske design ser flot ud og muliggør nem og billig installation.
- Fremtidssikrede forbindelsesmuligheder – udstyret med flere digitale og analoge signalindgange, der opfylder industristandarderne, for at sikre fleksibel integration i AV-infrastrukturer.
- Alenestående drift – displayet er designet til enkel, alenestående drift takket være integreret USB-medieafspiller, højttalere og planlægningsfunktion.
- Nem afspilning af indhold - den integrerede USB-medieafspiller understøtter forskellige billedvideofilformater for at sikre nem og alenestående afspilning af indhold.

Specifikationer

Accessories

| | |
|-------------------------------------|--|
| [AVSpecificationAccessories] | Remote Control Transmitter, Installation Set-Up Manual, Power Cord, HDMI Cable, Mounting Bracket, Tabletop Stand, Trolley Stand, Battery |
| Shipping Content | 2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual |
| Panel Technology | IPS with Direct LED backlights |
| Native Resolution (Pixels) | 3840 x 2160 |
| Aspect Ratio | 16:9 |
| Backlight Technology | Direct LED |
| Brightness (cd/m2) | 350 |
| Contrast Ratio | 8000:1 |
| Response Time (grey to grey avg) ms | 8 |
| Pixel Pitch (mm H/V) | 0,43 |
| Viewing Angle [°] | 178 |
| Colour Depth [bn] | 1073 (10bit) |
| Active Screen Area (H/V) mm | 1649.7 x 927.9 |
| Component | 1 |
| Composite | 1 |
| HDMI | 3 |
| Audio 3.5mm Jack | 1 |
| VGA | 1 |
| RS232C IN | 1 |
| LAN Port | 1 |
| USB | 1 |
| Colour Versions | Black Front Bezel, Black Back Cabinet |
| Operating Humidity (min) [%] | 20 |
| Operating Humidity (max) [%] | 80 |
| Energy Star | True |
| Haze Level [%] | Pro 25 |

Special Characteristics

| | |
|--|------------------|
| Limited Manufacturer's Warranty (yrs.) | 3 |
| Local Dimming | True |
| Built in Speakers (W) | 10 + 10 |
| Cabinet Colour | Black |
| Brightness Sensor | True |
| Scheduler / Timer | True |
| Gain Control | True |
| Operating Voltage(ACV) / Frequency(Hz) | 100-240 |
| Operating Voltage(ACV) / Frequency(Hz) | 50-60 |
| Power Consumption (W) (Operating MAX) | 145 |
| Operating Temperature (oC) | 0 - 40 |
| Storage Temperature [°C] | -20 - 60 |
| Storage Humidity [%] | 10 |
| Storage Humidity [%] | 90 |
| Landscape | True |
| Portrait | True |
| Mounting (VESA/Number of Points/Pitch mm) | 600 x 400 (FDMI) |
| Mounting (VESA/Number of Points/Pitch mm) | 4 |
| Mounting Screw Specification (Size/Max Length) | M8 |
| Diagonal Size (inches / cm) | 75 |
| Diagonal Size (inches / cm) | 189 |
| Bezel Size (L/R) mm | 14 |
| Bezel Size (U) mm | 15 |
| Product Weight Without Stand (Kg) | 36 |
| [AVSpecificationConnectivityOutputAudio35MmJack] | 1 |

