

Interactive Display

NEC MultiSync ME501 IR



- Moderne og slankt design – robust, men elegant, mulighed for diskret integration i hvilken som helst anvendelse og alle miljøer.
- Stærk og holdbar – termisk hærdet glas med blændefri belægning er modstandsdygtigt overfor hærværk og sikrer perfekt læsbarhed med reduceret genspejling og minimal synlighed af fingeraftryk.
- Sikker fjernstyring – styr dine enheder sikkert på afstand ved hjælp af NEC NaviSet Administrator 2. Administrér vedligeholdelsesbehovene proaktivt, og spar tid og ressourcer.
- Inspirerende touch-præstationer forbedrer brugeroplevelsen - de hurtige, stabile og robuste touch-præstationer understøtter op til 20 touch-punkter.
- Fremtidssikrede forbindelsesmuligheder – udstyret med flere digitale og analoge signalindgange, der opfylder industristandarderne, for at sikre fleksibel integration i AV-infrastruktur.

Specifikationer

DISPLAY MODULE DATA

Panel Technology	VA with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	50 / 125.7
Aspect Ratio	16:9
Backlight Technology	LED
Brightness (cd/m2)	400
Contrast Ratio	> 8000:1
Response Time (grey to grey avg) ms	8
Viewing Angle (H/V) @ CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1,073 (8bit + FRC)
Response Time (typ.) [ms]	8

TOUCH INTERFACE SPECIFICATION

Technology	Infrared Touch
Number of Touch Points	20
Coating / Filter	Anti-glare
Screen Hardness (H)	7
Operating System Compatibility	Android; Linux; Mac OS; Raspberry Pi; Windows
Light Transmission [%]	92 (+ / - 2 %)
Haze Level [%]	4
Touch Method	Finger; Gloves; Stylus (≥ 2 mm)
Data Interface	USB-HID
Palm Rejection	No
Windows Ink	No

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	18.95
Bezel Size (U/L) mm	20
Product Dimensions (W/H/D) mm	1,143 x 661.5 x 80
Product Weight Without Stand (Kg)	27.8

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	2
DisplayPort	1
Audio 3.5mm Jack	1

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	1

KEY SPECIFICATIONS

Special Characteristics	HDMI ARC; Powered USB Port (10 W)
Operating Time	18 / 7
Built in Speakers (W)	10 + 10
Power Management	•

POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)	100-240 / 50 / 60
Power Consumption (W) (Operating MAX)	85 shipping
Operating Temperature (oC)	0 to 35
Humidity (%)	20-80

INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	4; 400 x 400 (FDMI)

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio/Headphone 3.5mm Jack	1
----------------------------	---

ACCESSORIES

Pen	Yes
Shipping Contents	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual; USB cable

