



Interaktive displays

PN-L652B

PN-L652B er designet til møder, konstruktion, ingeniørdesign og krævende samarbejds miljøer og tilbyder en jævn og fantastisk oplevelse.

- BIG PAD for office meeting room, corporate boardroom and professional training room
- 65 (163.9cm) size with 3840 x 2160 pixels
- Pen-On-Paper user experience with responsive smooth 20-point touch
- 4K reading and writing user experience
- Integrated Android PC for whiteboard and other embedded touch applications
- Latest BYOD wireless collaboration via integrated Android PC or OPS slot
- Intuitive writing, drawing and annotation with Sharp Pen Software
- Brilliant eye-catching image content with large size and wide viewing angle

Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Operation Manual, Installation Set-Up Manual, Power Cord, USB Cable, Pen, Battery, Cable Clamp, Sharp Pen Software, Sharp Touch Viewing Software
Shipping Content	1 x 300 cm USB Cable, 2 x Passive Stylus, 2 x AAA batteries, Cable Clamps, Display, Remote Control, Bracket for Camera, Bracket for Mini PC, Power Cable

Panel Technology	LCD
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Screen Filter	AR
Backlight Technology	LED / Full Array
Brightness (cd/m2)	350
Contrast Ratio	4000:1
Display Colours	1070
Pixel Pitch (mm H/V)	0,372
Viewing Angle [°]	178
Active Screen Area (H/V) mm	1428.48 x 803.52

Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	330
Power Consumption (W) (Standby)	0,5
Operating Temperature (oC)	5 - 35
Storage Humidity [%]	20
Storage Humidity [%]	80
Heat Dissipation (BTU/h) MAX	1126

Landscape	True
Mounting (VESA/Number of Points/Pitch mm)	600 x 400
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M8

CE, CB Report	True
Mercury Content (mg)	True
Presence of Lead (Accepted application of RoHS Directive)	True

RS232C IN	1
LAN Port	1
USB	4

[AVSpecificationConnectivityOutputAudio35MmJack]1	
External Speaker	2

AirServer Embedded Screen Mirroring Solution

Airplay	Yes
---------	-----

Light Sensor Processing	-
-------------------------	---

Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10 + 10
Computer Input - Plug and Play	True
Power Management	True
Option Slot Interface	True
Equipment Space (Mounting)	True
Cabinet Colour	Black
Installation Handles	True
Fanless	True
Multi Language OSD	True
Scheduler / Timer	True
Remote Management	True
Adjustment Lock Feature	True
Auto Input Change	True
Self-Adjust	True
Monitor Control Software Support	True
Overscan Setting (AV)	True
Audio Selection per Image INPUT	True
Internal/External Speaker Selection	True
Operating Time	16/7

Antal beröringspunkter	20
Safety Glass Thickness (mm)	3,4
Pen Mode / Finger Mode	True
PC Connection Method	USB
Screen Hardness (H)	8
Operating System Compatibility	Windows 10, Windows 11, Mac OSX
Data Interface	USB-HID
Windows Ink	True
[AVSpecificationTechnology]	PrecisionTouch

Shipping Carton Dimensions (W/H/D) mm	1628
Shipping Carton Dimensions (W/H/D) mm	1005
Shipping Carton Dimensions (W/H/D) mm	208
Product Weight Without Stand (Kg)	37
Shipping Weight (Kg)	45

HDMI	3
Audio 3.5mm Jack	1
[AVSpecificationConnectivityInputUsbc]	1
VGA	1

Miracast	True
WLAN	True
Bluetooth	True

Bezel Size (L/R) mm	15
Bezel Size (U) mm	15
Bezel Size (L) mm	44

Diagonal Size (inches / cm)	65
Diagonal Size (inches / cm)	164