

Digital Signage

NEC MULTISYNC E438



De funktioner, du har brug for, til den pris, du ønsker.

- Slankt design og indbyggede højttalere – det æstetiske design ser flot ud og muliggør nem og billig installation.
- Fremtidssikrede forbindelsesmuligheder – udstyret med flere digitale og analoge signalindgange, der opfylder industristandarderne, for at sikre fleksibel integration i AV-infrastrukturer.
- Nem afspilning af indhold - den integrerede USB-medieafspiller understøtter forskellige billedvideofilformater for at sikre nem og alenestående afspilning af indhold.
- Professionel integration – med essentiel RS232-funktionalitet, IR- og knaplås og digital lydudgang S/PDIF kan skærmen nemt integreres i applikationer i offentlige miljøer.
- Alenestående drift – displayet er designet til enkel, alenestående drift takket være integreret USB-medieafspiller, højttalere og planlægningsfunktion.

Specifikationer

Accessories

[AVSpecificationAccessories]

Remote Control Transmitter, Installation Set-Up Manual, AC Adapter, Power Cord, HDMI Cable, Mounting Bracket, Tabletop Stand

Shipping Content

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Backlight Technology	Direct LED
Brightness (cd/m2)	350
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Pixel Pitch (mm H/V)	0,245
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Active Screen Area (H/V) mm	941 x 529

Power Consumption (W) (Operating MAX)	135
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	5
Storage Humidity [%]	85

Landscape	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 200 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6

Colour Versions	Black Front Bezel, Black Back Cabinet
-----------------	---------------------------------------

Operating Humidity (min) [%]	10
Operating Humidity (max) [%]	80

Energy Star	True
-------------	------

[AVSpecificationConnectivityOutputAudio35MmJack]1

Special Characteristics

Audio settings with equalizer, CEC Support, Colour temperature mode, Display Browser Control, Energy saving picture mode, HDMI with UHD at 60 Hz, HDR Gamma Support (HLG, PQ), Mac and Windows compatible, Powered USB-Port, PJLink Support, Scheduler, SNMP Support, HDMI ARC, User input priority definition

Limited Manufacturer's Warranty (yrs.)

Built in Speakers (W)	10 + 10
Cabinet Colour	Black
Temperature Sensor	True
Brightness Sensor	True
IP Rating	True
Scheduler / Timer	True

Component	1
Composite	1
HDMI	3
Audio 3.5mm Jack	1
VGA	1

Shipping Carton Dimensions (W/H/D) mm	1
Shipping Carton Dimensions (W/H/D) mm	1
Shipping Carton Dimensions (W/H/D) mm	0
Product Weight Without Stand (Kg)	9

RS232C IN	1
LAN Port	1
USB	1

Diagonal Size (inches / cm)	43
Diagonal Size (inches / cm)	108

Bezel Size (L/R) mm	13
Bezel Size (U) mm	14

Haze Level [%]	1
----------------	---

