

# This is Why



- ▶ FANLESS AND NOISELESS MODULAR RESTAURANT AND BAR/PUB POS SYSTEM
- ▶ LARGE 38 CM TRUE FLAT COLOUR TOUCH SCREEN
- ▶ COMPACT AND POPULAR DESIGN
- ▶ HIGH VISIBLE ADJUSTABLE LEFT/RIGHT AND UP/DOWN LED BACKLIGHT LCD TOUCH SCREEN
- ▶ SUPERIOR EASY TO CLEAN AND HIGH IP RATING LCD FRONT PANEL
- ▶ INTEL CELERON BAY-TRAILJ1900 CPU
- ▶ SATA 2.5" SOLID STATE DISK 64GB TRANSCEND STANDARD
- ▶ WINDOWS POSREADY 7 OPERATING SYSTEM PRE-INSTALLED

The RZ-X735F tailor made POS terminal is especially suitable for the restaurant and bar/pub market environment. The true flat touch screen surface allows easy cleaning and avoids dust or crumbs in the LCD frame. A lot of opportunities are offered with the flexible PC-based POS terminal RZ-X735F as it allows to install specific application software dedicated to the market segments.

Apart from this, the RZ-X735F can be upgraded to an overall sophisticated system. This, due to the availability of several interfaces to connect different printers, a 26 cm colour LCD customer display, magnet card reader, security by applying the Dallas clerk key system etc.

Not only visually, but also from the daily work and efficiency standpoint the RZ-X735F is perfectly designed. The terminal can be placed directly on the checkout desk or installed at the wall. Thanks to its fanless technology the RZ-X735F reduces energy cost to a significant low level.

## DISPLAY

- Color touch (cm): **38 with LED Backlight/300cd/m<sup>2</sup>**
- TFT Color LCD display: ✓
- Size 1: **1.024 x 768 (XGA)**
- Size 2: **not supported**

## NETVÆRK

- Ethernet 10 / 100 / 1000 Mbps: ✓/✓/✗

## TEKNISKE SPECIFIKATIONER

- Mål (B x D x H) (mm): **365 x 234 x 360**
- Vægt (kg.): **6.580kg**
- Strømforbrug Drift (W): **less than 84W**
- EMV Class: **This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.**

## PC SYSTEM

- Operating system: **Windows POSReady 7**
- CPU: **Intel Celeron Bay-Trail J1900 2.0 GHz/Fanless**
- L2 Cache: **1MB**
- BIOS ROM (Flash ROM): **AMI BIOS**
- Standard RAM Hukommelse: **2 GB**
- Maximum RAM Hukommelse: **8 GB**
- Alternative Drive: **SATA 2.5**
- Video RAM: ✓
- Magnet kortlæser: **optional**
- LPT parallel port: **1**
- Customer display: **optional external 2 line customer or 29 cm LCD customer display**
- Skuffe: **maximal 2**
- Håndholdte terminaler: ✓

## I/O PORTE

- Seriel RS232: **4**
- USB: **4**
- Ekstern monitor (VGA interface): **1**
- Operatør lås: **optional Dallas key system**