

Digital Signage

# SHARP MULTISYNC® P506 LCD 50" PROFESSIONAL LARGE FORMAT DISPLAY



Når pålidelighed, sikkerhed og exceptionel billedkvalitet er afgørende, leverer Sharp MultiSync® P6 serien præcision og robusthed.

- Forbedret farve og billedpræcision – når konsekvent farve og billedgengivelse er vigtig, giver Sharps's SpectraView Engine fuld kontrol over farver, gamma og ensartethed for korrekt og stabil billedkvalitet.
- Optimal læsbarhed – et high haze panel reducerer blænding fra vinduer og omgivende lys, så skiltindhold og præsentationer er tydelige og letlæselige i alle miljøer.
- Sikker netværkstilslutning – 802.1xunderstøttelse over LAN gør det muligt at tilslutte skærmen sikkert og kontrolleret, hvilket giver IT teamet et trygt driftsmiljø.
- Mission-kritisk ydeevne – med en lysstyrke på 700 cd/m<sup>2</sup>, komponenter med lang levetid og et robust, flammehæmmende metalchassis er P6-serien konstrueret til at levere vedvarende skarphed og høj modstandsdygtighed i krævende miljøer, uden behov for store beskyttelseskabinetter.
- Pålidelig integration – fuld kompatibilitet med førende AV-økosystemer, herunder Crestron XiO Cloud og NVX, Q-Sys, Cisco Webex, Matrox IPMX samt forskellige CMS-løsninger, sikrer nem installation og fremtidssikret skalerbarhed.

# Specifikationer

[AVSpecificationControlTerminals]	RS232C
Special Characteristics	CEC Support, HDMI ARC, Scheduler, DICOM Simulation, [clone-settings]
24/7 Operation Certified	True
Built in Speakers (W)	10 + 10
Power Management	True
Temperature Sensor	True
Remote Management	True
Operating Time	24/7
Frame Material	Metal
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz) Via AC Adapter	50-60 True
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	80
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
[AVSpecificationBattery]	< 0.5 (ECO Standby)
Portrait	True
Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	300 x 300 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6
[AVSpecificationFaceUp]	True
[AVSpecificationFaceDown]	True
Shipping Carton Dimensions (W/H/D) mm	1245
Shipping Carton Dimensions (W/H/D) mm	785
Shipping Carton Dimensions (W/H/D) mm	188
Product Weight Without Stand (Kg)	18
Shipping Weight (Kg)	23
Energy Efficiency	Energy Consumption: 85kWh/1000 h, LED backlight technology, Energy efficiency class: G
Ecological Standards	Energy Star 8.0
Bezel Size (L/R) mm	11
Bezel Size (U) mm	11
Bezel Size (L) mm	14
Horizontal Frequency [kHz]	15 - 135
Vertical Frequency [Hz]	23 - 76
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Power Consumption on-mode (IEC62087:2012)	95 (shipping)

Panel Technology	VA with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Brightness (cd/m2)	700
Contrast Ratio	8000:1
Pixel Pitch (mm H/V)	0,285
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Active Screen Area (H/V) mm	1095 x 616
Response Time (typ.) [ms]	8
Colour Versions	Black Front Bezel, Black Back Cabinet
Safety & Ergonomics	EMC Class B, UKCA, ISO 9241-307 (pixel failure class I), RoHS, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, REACH
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight, Optional 4th to 5th year warranty extension, [additional-services-available]
Supported Resolution	1270 x 720, 1920 x 2160, 1920 x 1200, 1024 x 768, 1280 x 1024, 1600 x 1200, 1920 x 1080, 640 x 480, 800 x 600, 1280 x 720, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1366 x 768, 1400 x 1050, 1280 x 800, 4096 x 2160
<b>Accessories</b>	
[AVSpecificationAccessories]	[eco-sensor], [feet], [remote-control-kit], [soundbar], [speaker], [trolley], [usb-c-cable], [wall-mount]
Shipping Content	Setup Manual, 2 x AAA batteries, HDMI Cable, Remote Control, Display, Power Cable
Diagonal Size (inches / cm)	50
Diagonal Size (inches / cm)	126
Colour Gamuts	86% of DCI
Digital	DisplayPort, DisplayPort out, HDMI, USB Type C
Output Control	LAN 100Mbit
[AVSpecificationLandscapeDimensionsWidthMm]	1122
[AVSpecificationLandscapeDimensionsHeightMm]	645
[AVSpecificationLandscapeDimensionsDepthMm]	67
Built in Speakers (W)	Internal 10W + 10W
Haze Level [%]	Pro 25

