



Big Pad Interaktive displays

# PN-70HC1E

Sharp's 4K BIG PAD PN-70HC1E has been developed for classrooms or higher education campuses as well as meeting rooms and workspaces.

- 4K BIG PAD for Education, Training and Meeting rooms
- 70 (176,6cm) size with 3840 x 2160 pixels
- Fast and responsive Infrared (IR) 10 point touch
- Two built-in (10W) stereo loudspeakers which clearly and effectively fill larger rooms
- Integrated SOC Controller player for PC-less Whiteboarding and Media playback
- OPS Slot for optional function enhancement
- Provides a natural 'Pen-on-Paper' experience using a passive pen or finger
- Intuitive control with full bezel button controls and on screen touch menu

# Specifikationer

## Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, USB Cable, Pen, Battery
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10 + 10
Computer Input - Plug and Play	True
Option Slot Interface	True
Cabinet Colour	Black
Fanless	True
Multi Language OSD	True
Adjustment Lock Feature	True
Screen Adjustment	True
Number of Touch Points	10
Number of Simultaneous Users	1
Safety Glass Thickness (mm)	4
Pen Mode / Finger Mode	True
PC Connection Method	USB 2.0
Operating System Compatibility	Windows 10
[AVSpecificationTechnology]	Infrared
Landscape	True
Mounting (VESA/Number of Points/Pitch mm)	600 x 400
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6
Bezel Size (L/R) mm	45
Bezel Size (U) mm	45
Bezel Size (L) mm	80
[AVSpecificationConnectivityOutputAudio35MmJack]1	
VGA	1
LAN Port	1
USB	1
Light Sensor Processing	-

Panel Technology	TFT-LCD
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Screen Filter	AR
Backlight Technology	LED / Edge Lit
Brightness (cd/m2)	350
Contrast Ratio	4000:1
Display Colours	1070
Response Time (grey to grey avg) ms	8
Pixel Pitch (mm H/V)	0,401
Active Screen Area (H/V) mm	1538.9 x 865.6

Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	400
Power Consumption (W) (Standby)	0,5
Operating Temperature (oC)	5 - 35
Storage Humidity [%]	20
Storage Humidity [%]	80
Heat Dissipation (BTU/h) MAX	1365
Power consumption off mode (IEC 62301:2005)	0

Shipping Carton Dimensions (W/H/D) mm	1765
Shipping Carton Dimensions (W/H/D) mm	1101
Shipping Carton Dimensions (W/H/D) mm	216
Product Weight Without Stand (Kg)	54
Shipping Weight (Kg)	68

HDMI	3
Audio 3.5mm Jack	1
VGA	2

CE, CB Report	True
Mercury Content (mg)	True

Miracast	True
WLAN	True

Diagonal Size (inches / cm)	70
Diagonal Size (inches / cm)	177

