

Desktop displays

# MULTISYNC E244F



Prioritering af brugerkomfort og levering af pålidelig ydeevne, E-serien er en perfekt løsning til hjemmekontoret og små til mellemstore virksomheder.

- Omkostnings- og tidsbesparende drift – baseret på et intuitivt OSD-design, der gør opsætningen enklere.
- Ergonomisk – fuld højdejusterbarhed (120 mm), dreje-, vippe- og drejefunktionalitet sikrer den perfekte individuelle arbejdspladsopsætning.
- Sort og hvid farveversioner – hvid anses at reducere indtrykket af tunnelsyn, når den placeres foran en hvid baggrund, såsom kontorvægge.
- Sikring af brugerens velvære – indbygget Low Blue Light-teknologi filtrerer farlige blå lysudslip, mens Flicker-Free-teknologi eliminerer baggrundsbelysningens flimrer, hvilket beskytter brugernes øjn
- Bedst i form og funktion – fremtidssikkert design med 3-sidet ultratynd ramme, tilgængelig i sort eller hvid, som supplerer en frisk professionel kontorindretning.

# Specifikationer

Panel Technology	VA TFT with W-LED backlight
Aspect Ratio	16:9
Brightness (cd/m2)	250
Contrast Ratio	3000:1
Pixel Pitch (mm H/V)	0,249
Response Time (typ.) [ms]	6
Screen Tilt [°]	-5 - 25
Height adjustable stand [mm]	120
Screen Swivel [°]	-170 - 170
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	541
[AVSpecificationLandscapeDimensionsHeightMm]	501
[AVSpecificationLandscapeDimensionsDepthMm]	233
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	RoHS compliant
Product Weight Without Stand (Kg)	4
Product Weight With Stand (Kg)	6
<b>Accessories</b>	
Shipping Content	Power Cable, DisplayPort Cable, Setup Guide
Digital	DisplayPort, HDMI
Analog	D-sub 15 pin
Bezel Size (L/R) mm	3
Bezel Size (L) mm	17
Power Supply	Integrated Power Supply

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable), Headphone Jack
Safety & Ergonomics	ISO 9241-307 (pixel failure class I), Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE, EnergyStar 8.0, Flicker-free
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight
Operating Temperature (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
Mounting (VESA/Number of Points/Pitch mm)	100 x 100
Kensington Lock	True
Diagonal Size (inches / cm)	22
Colours [Mio.]	16
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Vertical Frequency [Hz]	50 - 75
Optimum Resolution	1920 x 1080 at 60 Hz

