

Digital Signage

SHARP MULTISYNC® E659 LCD 65" ESSENTIAL LARGE FORMAT DISPLAY



Sharp MultiSync® E9-serien er indgangsniveauet for professionelle displayløsninger og er udviklet til moderne arbejdsmiljøer, der har behov for mere end det, en almindelig forbruger TV kan tilbyde.

- Optimal læsbarhed – et high haze panel reducerer blænding fra vinduer og omgivende lys, så skiltindhold og præsentationer er tydelige og letlæselige i alle miljøer.
- Standardiseret funktionalitet – deler samme design, betjening og enhedsstyring som øvrige skærme i Sharps displayportefølje, hvilket sikrer en ensartet brugeroplevelse og problemfri fjernstyring.
- Nem plugandplay skiltning – den integrerede USBmedieafspiller gør det muligt at afspille UHD indhold direkte med autostart, så digital skiltning kan startes med det samme uden ekstern hardware eller CMS.
- Fleksibel orientering – designet til både stående og liggende installation, med en ramme der har samme bredde hele vejen rundt for et rent og professionelt udtryk.

Specifikationer

Bezel Size (L/R) mm	11
Bezel Size (U/L) mm	11
Response Time (grey to grey avg) ms	8
Special Characteristics	USB Media Player, NaViSet Administrator 2, CEC Support, Powered USB-Port, HDMI ARC, Scheduler
Built in Speakers (W)	10 + 10
Remote Management	True
Operating Time	16/7
[AVSpecificationSupportedImageFormats]	Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK)
Portrait	True
Landscape	True
Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 400 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6
Supported Resolution	1920 x 1200, 1024 x 768 , 1280 x 1024, 1920 x 1080, 640 x 480, 1280 x 720, 1280 x 960, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1400 x 1050, 1280 x 800, 4096 x 2160
Shipping Carton Dimensions (W/H/D) mm	1635
Shipping Carton Dimensions (W/H/D) mm	987
Shipping Carton Dimensions (W/H/D) mm	160
Shipping Weight (Kg)	23
Bezel Size (L/R) mm	11
Bezel Size (U) mm	11
Bezel Size (L) mm	11
Diagonal Size (inches / cm)	65
Diagonal Size (inches / cm)	164
Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	24 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationWeightKg]	17

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Brightness (cd/m2)	350
Contrast Ratio	1200:1
Pixel Pitch (mm H/V)	0,372
Viewing Angle [°]	178
Colour Depth [bn]	1.07 (8bit + FRC)
Active Screen Area (H/V) mm	1428.48 x 803.52
Response Time (typ.) [ms]	8

Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Via AC Adapter	True
Operating Voltage(DCV)	100-240
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	80
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
[AVSpecificationBattery]	< 0.5 (ECO Standby)

Colour Versions	Black Back Cabinet, Black Front Bezel
Safety & Ergonomics	UKCA, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, VCCI, RCM
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight

Accessories

[AVSpecificationAccessories]	[feet], [wall-mount], [usb-c-cable], [trolley]
Shipping Content	Power Cable, Remote Control, 2 x AAA batteries, Setup Manual, Display

Energy Efficiency	LED backlight technology, Energy consumption: 115 kWh/1000 h, Energy efficiency class: G
Ecological Standards	Energy Star 8.0

[AVSpecificationLandscapeDimensionsWidthMm]	1453
[AVSpecificationLandscapeDimensionsHeightMm]	829
[AVSpecificationLandscapeDimensionsDepthMm]	60

Power Consumption on-mode (IEC62087:2012)	125 (shipping)
Power Supply	100-240 V

Haze Level [%]	Pro 25
----------------	--------

Digital	HDMI, USB Type C
---------	------------------

