

Digital Signage

NEC MULTISYNC MA431



Grundigt kraftfuld skiltning.

- Uhindret læsbarhed – ingen genspejling fra vinduer eller andre lyskilder betyder, at skiltens indhold eller præsentationen i mødelokalet hele tiden er synlige.
- Stort farveområde – den højtydende panelteknologi leverer et bredt udvalg af farver for at sikre en udsøgt visuel oplevelse.
- Sikker på offentlige steder – takket være en metalafdækning bagtil og intelligent varmestyring er den sikker at anvende på offentlige steder, hvor der er krav om brandbeskyttelse.
- Forbedret visning af billeder - avancerede indstillinger af relevante, visuelle parametre giver mulighed for fuld kontrol af lysstyrke, farve, gamma og ensartethed via SpectraView Engine for præcise,
- Missionskritisk, klar til drift 24/7 – valget af industrielle komponenter og omhyggeligt design fokuseret på svære anvendelsesscenarier går hånd i hånd med en imponerende og uafbrudt brugeroplevelse.


Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, Brightness Sensor, Mounting Bracket, Tabletop Stand, Trolley Stand
Shipping Content	2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual
Panel Technology	IPS with Edge LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Brightness (cd/m2)	500
Contrast Ratio	8000:1
Response Time (grey to grey avg) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Landscape	True
Portrait	True
Horizontal	True
Mounting (VESA/Number of Points/Pitch mm)	300 x 300 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6
DisplayPort	2
HDMI	2
Audio 3.5mm Jack	1
RS232C IN	1
LAN Port	1
USB	3
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Energy Star	True
Haze Level [%]	28

Special Characteristics

Limited Manufacturer's Warranty (yrs.)	3
Local Dimming	True
Power Management	True
Equipment Space (Mounting)	True
Cabinet Colour	Black
Temperature Sensor	True
Brightness Sensor	True
IP Rating	True
Picture in Picture Mode	True
Picture by Picture Mode	True
Scheduler / Timer	True
Remote Management	True
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	70
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	90
Shipping Carton Dimensions (W/H/D) mm	1120
Shipping Carton Dimensions (W/H/D) mm	700
Shipping Carton Dimensions (W/H/D) mm	203
Product Weight Without Stand (Kg)	19
Shipping Weight (Kg)	23
DisplayPort	1
HDMI	1
[AVSpecificationConnectivityOutputAudio35MmJack]	1
Diagonal Size (inches / cm)	43
Diagonal Size (inches / cm)	108
Bezel Size (L/R) mm	11
Bezel Size (U) mm	16



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: NEC MultiSync MA431, 19/5/2026