

Interactive Display

NEC MultiSync WD551



- Bring your own meeting (BYOM) – en enkel, samlet løsning til øjeblikkelig start af møder ved hjælp af hvilken som helst enhed.
- Certificeret til Microsoft Teams og mere – en problemfri BYOM-løsning kører videomøder via din foretrukne konferenceplatform.
- Smart styring af rum – opnå maksimal komfort i dine møderum, og oprethold optimale miljømæssige parametre, idet du bruger de indbyggede IoT-sensorer til at administrere analyserne i alle dine mødeloka
- Forbindelse uden problemer og besvær – et enkelt, sikkert USB-C-kabel forbinder din enhed med displayet for automatisk synkronisering af det indbyggede kamera, højttalerne, mikrofonen, touchskærm og p
- Naturlig touch-fornemmelse, nem at gøre ren – det rengøringsvenlige, flugtende skærmdesign reducerer parallaxse og giver en fantastisk skriveoplevelse, idet det understøtter Windows Ink med to inklude

Specifikationer

DISPLAY MODULE DATA

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	55 / 138.78
Aspect Ratio	16:9
Backlight Technology	LED
Brightness (cd/m2)	400
Contrast Ratio	1200:1
Viewing Angle (H/V) @ CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1,073 (10bit)
Response Time (typ.) [ms]	8

TOUCH INTERFACE SPECIFICATION

Technology	PCAP
Number of Touch Points	20
Coating / Filter	Anti-glare
Screen Hardness (H)	7
Operating System Compatibility	Android; Linux; Mac OS; Windows
Light Transmission [%]	≥ 88
Haze Level [%]	4 ~ 10
Reflection Rate [%]	4
Touch Method	Active Stylus; Conductive Passive Stylus (≥ 8 mm); Finger
Palm Rejection	No
Data Interface	USB-HID
Windows Ink	Yes

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	Edge-to-edge flush design (no bezel)
Bezel Size (U/L) mm	Edge-to-edge flush design (no bezel)
Product Dimensions (W/H/D) mm	1,266 x 856.7 x 85.1
Product Weight Without Stand (Kg)	31.2

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	1
------	---

CAMERA

Viewing Angle [°]	120 diagonal / 113 horizontal / 81 vertical
Resolution	Output HD 3840p 30fps

KEY SPECIFICATIONS

Special Characteristics	Collaboration Display; Microsoft Teams Certified
Operating Time	16 / 7
Built in Speakers (W)	12 W + 12 W

POWER SUPPLY AND OPERATING ENVIRONMENT

Power Consumption (W) (Operating MAX)	371
Operating Temperature (°C)	+0 to +40
Humidity (%)	10 to 90

INSTALLATION

Landscape	•
Mounting (VESA/Number of Points/Pitch mm)	4; 400 x 200 (FDMI)

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	2

MICROPHONE/ECHO-CANCELLING

Array	built-in 6 array
Distance [m]	6
Degrees [°]	180

