

Desktop displays

SHARP/NEC MULTISYNC EA241F



Ideel til brug med flere skærme med en smal ramme og elegant udseende, EA241F maksimerer produktiviteten med bedste ergonomi i sin klasse.

- Eftertragtet skærmstørrelse – den populære 23,8-tommers skærm med Full HD-opløsning er den perfekte størrelse til travle kontorarbejdspladser.
- Bedst i form og funktion – fremtidsklar design med 3-sidet ultratynd ramme, tilgængelig i sort eller hvid, som komplementerer et friskt professionelt kontorinteriør.
- Energieffektivitet – reducer dit energiforbrug med op til 30% ved at aktivere de indbyggede menneske- og omgivelseslysensorer, som sikrer, at skærmen kun er tændt i henhold til brugsforholdene.
- Maksimal opmærksomhed på sundhed og velvære – den ergonomiske højdejustering fra 0 til 150 mm; indbygget Low Blue Light og Flicker-Free teknologi; plus integreret omgivelseslyssensor kombineres for at
- Nem kontrol af flere skærme – administrer indstillingerne for op til 5 skærme i en multi-monitor konfiguration via hovedskærmen med ControlSync®-teknologi.

Specifikationer

Panel Technology	IPS TFT with W-LED backlight
Aspect Ratio	16:9
Brightness (cd/m2)	250
Contrast Ratio	1000:1
Pixel Pitch (mm H/V)	0,275
Response Time (typ.) [ms]	5
Screen Tilt [°]	-5 - 25
Height adjustable stand [mm]	150
Screen Swivel [°]	170 - -170
Screen Rotate [°]	0 - 90
[AVSpecificationPortraitDimensionsWidthMm]	319
[AVSpecificationPortraitDimensionsHeightMm]	615
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	319
[AVSpecificationLandscapeDimensionsHeightMm]	615
[AVSpecificationLandscapeDimensionsDepthMm]	250
Energy Efficiency	Energy efficiency class: C, Human sensor, Ambient light sensor, Energy consumption: 11 kWh/1000 h
Ecological Standards	Energy Star 8.0, ErP compliant, RoHS compliant, TCO 9.0, WEEE
Accessories	
Shipping Content	Power Cable, Setup Manual, DisplayPort Cable, USB cable, Control Sync Cable, Monitor
Digital	DisplayPort, HDMI, USB ver. 3.1 (2 down / 1 up), DVI-D
Analog	D-sub 15 pin
Power Supply	100-240 V, Internal Power Supply, 0.9 A/0.5 A
Bezel Size (L/R) mm	1
Bezel Size (L) mm	15
Optimum Resolution	1920 x 1080 at 60 Hz

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	VESA DDC2Bi, DDC2B/2Bi, VESA DDC/CI
Audio	Integrated Speakers (1 W + 1 W)
Adjust Functions	Advanced NTA (Advanced Non-Touch-Auto-Adjustment)
Safety & Ergonomics	ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TÜV Ergonomics, UL/C-UL or CSA, TCO 8.0, WEEE, CE, EAC, EnergyStar 8.0, ErP, Flicker-free
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight, Optional 1st to 3rd year 24/7 usage warranty, Optional 4th to 5th year warranty extension
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
Diagonal Size (inches / cm)	24
Colours [Mio.]	16
Colour Gamuts	72% NTSC, 101.6 % sRGB, 75.3% AdobeRGB
Frame Material	Aluminum alloy (front); metal (back)
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Mounting (VESA/Number of Points/Pitch mm)	100 x 100

