

Digital Signage Display

Sharp MultiSync PN-ME752



- Problemfri tilslutning – indbygget USB-C understøtter Bring Your Own Device-workflows, der sikrer inklusion og øger produktiviteten med en enkelt kabelforbindelse mellem notebook og skærm.
- Hurtig inputdetektion – fjerner potentiel frustration og udjævner vejen til produktive møderesultater, skærmen reagerer med det samme, når en enhed er tilsluttet.
- New feature-ready – regular OTA Android OS updates ensure availability of the latest features and system security.
- Bedste læsbarhed – og hjælper med høj produktivitet i veloplyste mødelokaler, et filter med høj uklarhed eliminerer genskin og refleksioner fra vinduer og andre lyskilder.
- Tredjepartskompatibilitet – ikke blot en skærm, men en klar løsning, der er kompatibel med populære arbejdsplads- og indholdsstyringssystemer via den integrerede SoC-plattform.

Specifikationer

DISPLAY MODULE DATA

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	75 / 189.3
Aspect Ratio	16:9
Backlight Technology	LED
Brightness (cd/m2)	450
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Viewing Angle (H/V)0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (8bit + FRC)
Haze Level [%]	Pro (25)

POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)	100-240 V AC; 50 / 60 Hz
Power Consumption (W) (Operating MAX)	132 shipping
Operating Temperature (oC)	0 to 40
Storage Temperature [°C]	-20 to 60
Humidity (%)	20 to 80
Storage Humidity [%]	10 to 90

INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	800 x 600 (FDMI); 4 holes

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

HDMI	1
Audio/Headphone 3.5mm Jack	1

ACCESSORIES

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Remote Control Transmitter	Yes
Power Cord	Yes
Mounting Bracket	Optional
Tabletop Stand	Optional
Battery	Yes

KEY SPECIFICATIONS

Special Characteristics	DICOM Simulation; HDMI ARC; Powered USB Port (15 W); Removable Logo
HDR High Dynamic Range	HDR10; HLG; PQ
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10 W + 10 W
Power Management	•
Cabinet Colour	Black
Colour Versions	Pantone (Process Black M)

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	15.9
Bezel Size (U/L) mm	15.9
Product Dimensions (W/H/D) mm	1,686 x 964 x 68
Shipping Carton Dimensions (W/H/D) mm	1,863 x 1,090 x 225
Product Weight Without Stand (Kg)	34.3
Shipping Weight (Kg)	51

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	3
Audio 3.5mm Jack	1
Other	1 x USB-C

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	3