

Desktop displays

SHARP / NEC MULTISYNC EA271F



Fremtidssikret, professionel kontorproduktivitet, der kombinerer optimal visning med fremragende ergonomi.

- Ergonomisk kontor – mulighed for fuld højdejustering (150 mm), sving-, hælde- og drejefunktion sikrer perfekt, individuel, ergonomisk opsætning.
- Beskyttelse af dine øjne mod træthed og skader - Indbygget lavt blå lys-teknologi bortfiltrerer farlig udledning af blåt lys, mens flimmerfri teknologi fjerner enhver flimren i baggrundsbelysningen.
- Bedst i form og funktion - et fremtidsklart design med 3-sidet, ultrasmal pynteramme, der kan fås i sort eller hvid og matcher kontorets friske, professionelle indretning.
- Nem styring af flere skærme - håndterer indstillingerne af op til 5 skærme i en konfiguration med flere skærme via hovedskærmen med ControlSync® teknologi.
- Maksimér billedkvaliteten med Uniformity Control – opnå en perfekt ensartethed over hele opsætningen med flere skærme med bare ét klik i skærmmenuen på selve skærmen.

Specifikationer

Panel Technology	AH-IPS LCD with LED backlight
Aspect Ratio	16:9
Brightness (cd/m2)	250
Contrast Ratio	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
Display Colours	16.78
Response Time (grey to grey avg) ms	6
Pixel Pitch (mm H/V)	0,311
Energy Efficiency	Ambient light sensor, Auto brightness, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 11 kWh/1000 h, Energy efficiency class: C, Human sensor, LED backlight technology
Ecological Standards	Efficient mechanical design for minimised packaging, Minimal use of harmful material
Ecological Materials	Energy Star 8.0, ErP compliant, TCO 8.0, WEEE
Special Characteristics	ControlSync®, Carbon Savings Meter, DICOM preset, Customize Setting, DDC/CI compatible, RGB Support, Frame Comp, ErgoDesign®, LED Backlight Technology, Picture-by-Picture, PLink Support, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Touch Sensor Keys, USB ver. 3.0 (3 down / 1 up), Flicker Free
Optimum Resolution	1920 x 1080 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 720 x 400 (70 Hz), 800 x 600
Operating Temperature (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Diagonal Size (inches / cm)	27
Diagonal Size (inches / cm)	69
Colour Gamuts	102 % sRGB, 75.5% AdobeRGB, 72% NTSC
Digital	DisplayPort, DVI-D, HDMI, USB ver. 3.1 (3 down / 1 up)
Analog	VGA
Mounting (VESA/Number of Points/Pitch mm)	100 x 100
Kensington Lock	True

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	DDC2B/2Bi, EDID Standard, VESA DDC/CI
Audio	Headphone Jack, Integrated Speakers (1 W + 1 W)
Adjust Functions	Audio Volume / Lock-Out, Auto Adjust, Lysstyrke, Colour Temperature Control, Kontrast, Control Sync, DV Mode, EcoMode, Factory Preset, Fine Adjust (analog), Human Sensing, Intelligent Power Management, Language Select, Monitor Information, NTAA (Non-Touch-Auto-Adjustment), On-Screen-Display (OSD) lock-out, One Touch Recovery, Power-Off Timer, sRGB CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class 2), ISO 9241-307 (pixel failure class 1), Low Blue Light, PSB, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Safety & Ergonomics	
Limited Manufacturer's Warranty (yrs.)	3 years warranty incl. backlight, Optional 1st to 3rd year 24/7 usage warranty, Optional 4th to 5th year warranty extension
Optional Accessories	MDSVSENSOR Value
Height adjustable stand [mm]	150
Screen Swivel [°]	-170 - Value
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	360
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	628
[AVSpecificationPortraitDimensionsHeightMaxMm]	653
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
Accessories	
Shipping Content	Control Sync Cable, DisplayPort Cable, Monitor, Power Cable, Setup Manual, Setup Guide, USB cable
Power Consumption on-mode (IEC62087:2012)	12 (Eco Mode 2), 17 (Eco Mode), 17 (typ.), 45 (max.)
Power Supply	0.85 A/0.45 A, 100-240 V, Integrated Power Supply
Product Weight Without Stand (Kg)	5
Product Weight With Stand (Kg)	8
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75

Operating Humidity (min) [%] 20
Operating Humidity (max) [%] 80

Bezel Size (L/R) mm 1
Bezel Size (U) mm 1



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp / NEC MultiSync EA271F, 23/6/2026