

Digital Signage

SHARP MULTISYNC PN-ME752



For enestående ydeevne i mødelokaler og digitale skilteløsninger tilbyder ME-serien klassens bedste visuelle ydeevne

- Problemfri tilslutning – indbygget USB-C understøtter Bring Your Own Device-workflows, der sikrer inklusion og øger produktiviteten med en enkelt kabelforbindelse mellem notebook og skærm.
- Bedste læsbarhed – og hjælper med høj produktivitet i veloplyste mødelokaler, et filter med høj uklarhed eliminerer genskin og refleksioner fra vinduer og andre lyskilder.
- Hurtig inputdetektion – fjerner potentiel frustration og udjævner vejen til produktive møderesultater, skærmen reagerer med det samme, når en enhed er tilsluttet.
- Tredjepartskompatibilitet – ikke blot en skærm, men en klar løsning, der er kompatibel med populære arbejdsplads- og indholdsstyringssystemer via den integrerede SoC-platform.
- New feature-ready – regular OTA Android OS updates ensure availability of the latest features and system security.

Specifikationer

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Backlight Technology	LED
Brightness (cd/m2)	450
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1073 (8bit + FRC)
<hr/>	
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	132
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	80
<hr/>	
Product Weight Without Stand (Kg)	35
Shipping Weight (Kg)	51
<hr/>	
HDMI	0
Audio/Headphone 3.5mm Jack	1
<hr/>	
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
<hr/>	
Audio 3.5mm Jack	1

Special Characteristics	DICOM Simulation, HDMI ARC, Powered USB Port (15 W), Removable Logo
HDR High Dynamic Range	HDR10, HLG, PQ
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10 + 10
Power Management	True
Equipment Space (Mounting)	True
Cabinet Colour	Black
Scheduler / Timer	True
Remote Management	True
<hr/>	
Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	800 x 600 (FDMI)
Mounting Screw Specification (Size/Max Length)	M8
<hr/>	
Bezel Size (L/R) mm	16
Bezel Size (U) mm	16
Bezel Size (L) mm	16
<hr/>	
Diagonal Size (inches / cm)	75
Diagonal Size (inches / cm)	189
<hr/>	
Energy Star	True
<hr/>	
Haze Level [%]	Pro 25