

PN-HW651



Med Sharps digital informationsskærm PN-HW651 kan du nyde den perfekte kombination af elegant design og krystalklare billeder. Få dit budskab ud, højt og tydeligt, hvor som helst det skal ses.

- Få mere opmærksomhed med et 65 display i dit detail- eller forretningsmiljø
- Vis billeder og video i detaljer med 4K Ultra HD-opløsning (3840 x 2160 pixels)
- Forbedret og ægte gengivelse af farve vist fra en bredt farveskala
- Kontinuerlig visning af indhold i åbningstiden 16/7
- Vis og hør indhold nemt med integreret 4K USB medieafspiller og højttalere
- Seneste HDMI-tilslutning til 4K ved 60Hz
- Slankt, let og elegant design, der passer til enhver butikslokale eller møderum
- Fleksibel installation i portræt og landskab

Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Operation Manual, Installation Set-Up Manual, CD Rom, Power Cord, Battery, Cable Clamp, Portrait Mount Sticker Kit
Panel Technology	TFT-LCD
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Backlight Technology	W-LED / Full Array
Brightness (cd/m2)	350
Contrast Ratio	4000:1
Display Colours	1060
Response Time (grey to grey avg) ms	8
Pixel Pitch (mm H/V)	0,372
Viewing Angle [°]	178
Active Screen Area (H/V) mm	1428 x 803
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Operating Voltage(DCV)	205
Power Consumption (W) (Standby)	50
Operating Temperature (oC)	0 - 40
Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 400
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6
RS232C IN	1
LAN Port	1
USB	1
Diagonal Size (inches / cm)	65
Diagonal Size (inches / cm)	163
Audio RCA R-L	1

Built in Speakers (W)	10 + 10
Computer Input - Plug and Play	True
Power Management	True
Cabinet Colour	Black
Installation Handles	True
Fanless	True
Temperature Sensor	True
Residual Image Reduction Feature	True
Multi Language OSD	True
Scheduler / Timer	True
Real Time Clock	True
Remote Management	True
Adjustment Lock Feature	True
Displaying Use Time Feature	True
Screen Adjustment	True
Colour Temperature Adjustment	True
Gamma Adjustment	True
Self-Adjust	True
Hardware Diagnosis	True
Monitor Control Software Support	True
Temperature Control	True
Shipping Carton Dimensions (W/H/D) mm	1655
Shipping Carton Dimensions (W/H/D) mm	1078
Shipping Carton Dimensions (W/H/D) mm	280
Product Weight Without Stand (Kg)	28
Shipping Weight (Kg)	34
HDMI	3
Audio 3.5mm Jack	1
VGA	1
Bezel Size (L/R) mm	14
Bezel Size (U) mm	14
Bezel Size (L) mm	15
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
CE, CB Report	True

