

Digital Signage

SHARP MULTISYNC® E439 LCD 43" ESSENTIAL LARGE FORMAT DISPLAY



Sharp MultiSync® E9-serien er indgangsniveauet for professionelle displayløsninger og er udviklet til moderne arbejdsmiljøer, der har behov for mere end det, en almindelig forbruger TV kan tilbyde.

- Optimal læsbarhed – et high haze panel reducerer blænding fra vinduer og omgivende lys, så skiltindhold og præsentationer er tydelige og letlæselige i alle miljøer.
- Standardiseret funktionalitet – deler samme design, betjening og enhedsstyring som øvrige skærme i Sharps displayportefølje, hvilket sikrer en ensartet brugeroplevelse og problemfri fjernstyring.
- Nem plugandplay skiltning – den integrerede USBmedieafspiller gør det muligt at afspille UHD indhold direkte med autostart, så digital skiltning kan startes med det samme uden ekstern hardware eller CMS.
- Fleksibel orientering – designet til både stående og liggende installation, med en ramme der har samme bredde hele vejen rundt for et rent og professionelt udtryk.

Specifikationer

| | |
|--|---|
| [AVSpecificationControlTerminals] | RS232C |
| Special Characteristics | NaViSet Administrator 2, CEC Support, USB Media Player, Powered USB-Port, HDMI ARC, Scheduler |
| Built in Speakers (W) | 10 + 10 |
| Remote Management | True |
| Operating Time | 16/7 |
| [AVSpecificationSupportedImageFormats] | Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK) |
| Colour Versions | Black Front Bezel, Black Back Cabinet |
| Safety & Ergonomics | UKCA, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, VCCI, RCM |
| Limited Manufacturer's Warranty (yrs.) | 3 years warranty incl. backlight |
| Accessories | |
| [AVSpecificationAccessories] | [feet], [trolley], [usb-c-cable], [wall-mount] |
| Shipping Content | Setup Manual, 2 x AAA batteries, Remote Control, Cable Clamps, Display, Power Cable |
| Shipping Carton Dimensions (W/H/D) mm | 1075 |
| Shipping Carton Dimensions (W/H/D) mm | 683 |
| Shipping Carton Dimensions (W/H/D) mm | 127 |
| Product Weight Without Stand (Kg) | 8 |
| Shipping Weight (Kg) | 11 |
| Energy Efficiency | Energy Consumption: 82kWh/1000 h, LED backlight technology, Energy efficiency class: G |
| Ecological Standards | Energy Star 8.0 |
| Diagonal Size (inches / cm) | 43 |
| Diagonal Size (inches / cm) | 108 |
| Horizontal Frequency [kHz] | 31.5 - 135 |
| Vertical Frequency [Hz] | 24 - 75 |
| Operating Humidity (min) [%] | 20 |
| Operating Humidity (max) [%] | 80 |

| | |
|--|---|
| Panel Technology | IPS with Direct LED backlights |
| Native Resolution (Pixels) | 3840 x 2160 |
| Aspect Ratio | 16:9 |
| Brightness (cd/m2) | 350 |
| Contrast Ratio | 1200:1 |
| Pixel Pitch (mm H/V) | 0,245 |
| Viewing Angle [°] | 178 |
| Colour Depth [bn] | 1.07 (8bit + FRC) |
| Active Screen Area (H/V) mm | 941 x 529 |
| Response Time (typ.) [ms] | 8 |
| Operating Voltage(ACV) / Frequency(Hz) | 100-240 |
| Operating Voltage(ACV) / Frequency(Hz) | 50-60 |
| Via AC Adapter | True |
| Operating Temperature (oC) | 0 - 40 |
| Storage Temperature [°C] | -20 - 60 |
| Storage Humidity [%] | 10 |
| Storage Humidity [%] | 80 |
| [AVSpecificationPowerSavingModeW] | < 2 (Networked Standby) |
| [AVSpecificationBattery] | < 0.5 (ECO Standby) |
| Supported Resolution | 1920 x 1200, 1024 x 768, 1280 x 1024, 1920 x 1080, 640 x 480, 1280 x 720, 1280 x 960, 1440 x 900, 1680 x 1050, 3840 x 2160, 1360 x 768, 720 x 576, 720 x 400, 720 x 480, 1400 x 1050, 1280 x 800, 4096 x 2160 |
| Landscape | True |
| Portrait | True |
| Mounting (VESA/Number of Points/Pitch mm) | 200 x 200 (FDMI) |
| Mounting (VESA/Number of Points/Pitch mm) | 4 |
| Mounting Screw Specification (Size/Max Length) | M6 |
| Bezel Size (L/R) mm | 11 |
| Bezel Size (U) mm | 11 |
| Bezel Size (L) mm | 11 |
| [AVSpecificationLandscapeDimensionsWidthMm] | 965 |
| [AVSpecificationLandscapeDimensionsHeightMm] | 555 |
| [AVSpecificationLandscapeDimensionsDepthMm] | 60 |
| Digital Output Control | HDMI, USB Type C LAN 100Mbit |
| Haze Level [%] | Pro 25 |
| Power Consumption on-mode (IEC62087:2012) | 85 (shipping) |

