

Desktop displays

SHARP / NEC MULTISYNC E243F



Den ergonomiske kommunikationshub til arbejdsrummet.

- Nyeste USB-tilslutningsstandard af type C - optimér tilslutningen, og erstat video-, lyd-, strøm- og USB-kablet med blot ét kabel til at forbinde din bærbare/tablet med skærmen.
- Fremtidssikret fleksibilitet – flere tilslutningsmuligheder giver en høj fleksibilitet med DP, HDMI, USB type C, USB A og lydudgang.
- Beskyttelse af brugernes velvære – indbygget lavt blå lys-teknologi bortfiltrerer farlig udledning af blå lys, mens flimmerfri teknologi fjerner enhver flimren i baggrundsbelysningen.
- Ergonomisk kontor – mulighed for fuld højdejustering (130 mm), sving-, hælde- og drejefunktion sikrer en perfekt, individuel, ergonomisk opsætning.
- Bedst i form og funktion - fremtidsklart design med en 3-sidet, ultrasmal ramme, fås i sort eller hvid, plus valgfri VESA-beslagplade til tynde kundenheder.

Specifikationer

Panel Technology	IPS TFT with W-LED backlight
Aspect Ratio	16:9
Brightness (cd/m2)	250
Contrast Ratio	1000:1
Display Colours	16.77
Response Time (grey to grey avg) ms	6
Pixel Pitch (mm H/V)	0,275
Viewing Angle [°]	178
Height adjustable stand [mm]	130
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	538
[AVSpecificationLandscapeDimensionsDepthMm]	190
[AVSpecificationLandscapeDimensionsHeightMinMm]	333
[AVSpecificationLandscapeDimensionsHeightMaxMm]	463
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, EcoMode, Energy consumption: 18 kWh/1000 h, Energy efficiency class: E
Special Characteristics	Low Blue Light, Local dimming, [usbc]
Accessories	
Shipping Content	DisplayPort Cable, Power Cable, Setup Guide, USB-C Cable
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Product Weight With Stand (Kg)	5

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play Audio	VESA DDC2Bi 1W + 1W (De-activateable), Headphone Jack
Adjust Functions	Auto Adjust, Lysstyrke, Carbon Footprint Meter, Carbon Savings Meter, DV Mode, EcoMode, Language Select
Safety & Ergonomics	EnergyStar 8.0, Flicker-free, Low Blue Light, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, WEEE
Operating Temperature (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Power Consumption on-mode (IEC62087:2012)	15 (Eco Mode 2), 15 (typ.), 20 (max.)
Power Supply	Integrated Power Supply
Mounting (VESA/Number of Points/Pitch mm)	100 x 100
Kensington Lock	True
Diagonal Size (inches / cm)	24
Diagonal Size (inches / cm)	60
Digital	DisplayPort, HDMI, USB Type C, USB ver. 3.1 (3 down / 1 up)
Bezel Size (L/R) mm	1
Bezel Size (U) mm	1
Optimum Resolution	1920 x 1080 at 60 Hz

