

Digital Signage

# SHARP/ NEC MULTISYNC ME652



For enestående ydeevne i mødelokaler og digitale skilteløsninger tilbyder ME-serien klassens bedste visuelle ydeevne og værdi for at understøtte dine behov.

- Problemfri tilslutning – indbygget USB-C understøtter Bring Your Own Device-workflows, der sikrer inklusion og øger produktiviteten med en enkelt kabelforbindelse mellem notebook og skærm.
- Bedste læsbarhed – og hjælper med høj produktivitet i veloplyste mødelokaler, et filter med høj uklarhed eliminerer blænding og refleksioner fra vinduer og andre lyskilder.
- Hurtig inputdetektion – fjerner potentiel frustration og udjævner vejen til produktive møderesultater, skærmen reagerer med det samme, når en enhed er tilsluttet.
- Tredjepartskompatibilitet – ikke blot en skærm, men en klar løsning, der er kompatibel med populære arbejdsplads- og indholdsstyringsystemer via den integrerede SoC-platform.
- Ny funktion klar – regelmæssige OTA Android OS-opdateringer sikrer tilgængeligheden af de nyeste funktioner og systemsikkerhed.

# Specifikationer

## Accessories

|  |  |
|--|--|
| [AVSpecificationAccessories]                     | Remote Control Transmitter, Installation Set-Up Manual, Power Cord, HDMI Cable, Mounting Bracket, Tabletop Stand, Trolley Stand, Battery |
| Shipping Content                                 | 2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual  |
| Panel Technology                                 | IPS with Direct LED backlights   |
| Native Resolution (Pixels)                       | 3840 x 2160  |
| Aspect Ratio                                     | 16:9   |
| Backlight Technology                             | LED  |
| Brightness (cd/m2)                               | 450  |
| Contrast Ratio                                   | 1200:1   |
| Response Time (grey to grey avg) ms              | 8  |
| Viewing Angle [°]                                | 178  |
| Colour Depth [bn]                                | 1073 (8bit + FRC)  |
| Shipping Carton Dimensions (W/H/D) mm            | 1628   |
| Shipping Carton Dimensions (W/H/D) mm            | 942  |
| Shipping Carton Dimensions (W/H/D) mm            | 185  |
| Product Weight Without Stand (Kg)                | 24   |
| Shipping Weight (Kg)                             | 35   |
| HDMI   | 0  |
| [AVSpecificationConnectivityOutputAudio35MmJack] | 1  |
| Audio/Headphone 3.5mm Jack                       | 1  |
| HDMI   | 3  |
| Audio 3.5mm Jack                                 | 1  |
| Operating Humidity (min) [%]                     | 20   |
| Operating Humidity (max) [%]                     | 80   |
| Energy Star                                      | True   |

|  |  |
|--|--|
| Special Characteristics                        | Frame Comp, Powered USB Port (10 W), Powered USB Port (5 W), Powered USB Port (15 W), HDR10, HLG, PQ |
| HDR High Dynamic Range                         |  |
| Limited Manufacturer's Warranty (yrs.)         | 3  |
| Built in Speakers (W)                          | 10 + 10  |
| Power Management                               | True   |
| Equipment Space (Mounting)                     | True   |
| Cabinet Colour                                 | Black  |
| Scheduler / Timer                              | True   |
| Remote Management                              | True   |
| Operating Voltage(ACV) / Frequency(Hz)         | 100-240  |
| Operating Voltage(ACV) / Frequency(Hz)         | 50-60  |
| Power Consumption (W) (Operating MAX)          | 140  |
| Operating Temperature (oC)                     | 0 - 40   |
| Storage Temperature [°C]                       | -20 - 60   |
| Storage Humidity [%]                           | 10   |
| Storage Humidity [%]                           | 90   |
| Landscape                                      | True   |
| Portrait                                       | True   |
| Mounting (VESA/Number of Points/Pitch mm)      | 600 x 400 (FDMI)   |
| Mounting (VESA/Number of Points/Pitch mm)      | 4  |
| Mounting Screw Specification (Size/Max Length) | M8   |
| RS232C IN                                      | 1  |
| LAN Port                                       | 1  |
| USB  | 4  |
| Diagonal Size (inches / cm)                    | 65   |
| Diagonal Size (inches / cm)                    | 164  |
| Bezel Size (L/R) mm                            | 16   |
| Bezel Size (U) mm                              | 16   |
| Haze Level [%]                                 | Standard 25  |