

This is Why



- ▶ FANLESS MODULAR RETAIL AND FAST FOOD POS SYSTEM
- ▶ LARGE 3.5 CM COLOUR TOUCH SCREEN
- ▶ COMPACT AND POPULAR DESIGN
- ▶ HIGH VISIBLE ADJUSTABLE LEFT/RIGHT AND UP/DOWN LCD TOUCH SCREEN
- ▶ SATA 2.5" HDD 160GB STANDARD
- ▶ 10/100/1000 BASE ETHERNET CONNECTION
- ▶ WAKE-ON LAN SUPPORT INCLUDING REMOTE BOOTING
- ▶ WEPOS READY 2009 OPERATING SYSTEM PRE-INSTALLED

Especially small and mid size companies must be highly flexible to survive in their daily business against larger companies. With the need of being active in the retail and fast food market, the flexible PC-based POS terminal RZ-X650 offers a lot of additional opportunities, as it allows to install specific application software dedicated to the market segments.

Apart from this, the RZ-X650 can be upgraded to an overall sophisticated system. This, due to the availability of several interfaces to connect different printers, a customer display, magnet card reader etc.

Not only visually, but also from the daily work and efficiency standpoint the RZ-X650 is perfectly designed. The terminal can be placed directly on the checkout desk or installed at the wall. Thanks to its fanless technology the RZ-X650 reduces energy cost to a significant low level.

DISPLAY

- Color touch (cm): **38**
- TFT Color LCD display: ✓
- Størrelse (dots) justerbart: ✓
- Size 1: **1.024 x 768 (XGA)**
- Size 2: **640 x 480 (VGA)**

NETVÆRK

- Ethernet 10 / 100 / 1000 Mbps: ✓/✓/✗

TEKNISKE SPECIFIKATIONER

- Mål (B x D x H) (mm): **380 x 311 x 320**
- Vægt (kg.): **6.65**
- Strømforbrug Drift (W): **max. 60 (without peripherals)**
- EMV Class: **This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.**

PC SYSTEM

- Operating system: **Windows XP Embedded POS READY 2009**
- CPU: **Intel ATOM 1.6 GHz**
- L1 Cache: **56 KB**
- L2 Cache: **512 KB**
- BIOS ROM (Flash ROM): **AMI BIOS**
- Standard RAM Hukommelse: **1 GB**
- Maximum RAM Hukommelse: **2 GB**
- Hard Disk: **160 GB**
- Video RAM: ✓
- Magnet kortlæser: **optional**
- LPT parallel port: **1**
- Customer display: **Optional external customer display**
- Skuffe: **maximal 2**
- Håndholdte terminaler: ✓

I/O PORTE

- Seriel RS232: **3**
- USB: **4**
- Ekstern monitor (VGA interface): **1**
- Operatør lås: **optional**