

Digital Signage

NEC MULTISYNC E328



De funktioner, du har brug for, til den pris, du ønsker.

- Reducerede installations- og driftsomkostninger – et yderst energieffektivt display med LED-baggrundsbelysning sikrer et lavere strømforbrug, baggrundsbelysning med en længere levetid og et lettere de
- Slankt design og indbyggede højttalere – det æstetiske design ser flot ud og muliggør nem og billig installation.
- Fremtidssikrede forbindelsesmuligheder – udstyret med flere digitale og analoge signalindgange, der opfylder industristandarderne, for at sikre fleksibel integration i AV-infrastrukturer.
- Nem afspilning af indhold - den integrerede USB-medieafspiller understøtter forskellige billedvideofilformater for at sikre nem og alenestående afspilning af indhold.
- Alenestående drift – displayet er designet til enkel, alenestående drift takket være integreret USB-medieafspiller, højttalere og planlægningsfunktion.

Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, HDMI Cable, Mounting Bracket, Tabletop Stand
Shipping Content	2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	1920 x 1080
Aspect Ratio	16:9
Brightness (cd/m2)	350
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Pixel Pitch (mm H/V)	0,364
Viewing Angle [°]	178
Active Screen Area (H/V) mm	698 x 393

Component	1
Composite	1
HDMI	3
Audio 3.5mm Jack	1
VGA	1

Landscape	True
Mounting (VESA/Number of Points/Pitch mm)	100 x 100 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6

Diagonal Size (inches / cm)	32
Diagonal Size (inches / cm)	80

Bezel Size (L/R) mm	13
Bezel Size (U) mm	14

[AVSpecificationConnectivityOutputAudio35MmJack]1

Special Characteristics

Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	5 + 5
Cabinet Colour	Black
Temperature Sensor	True
Brightness Sensor	True
IP Rating	True
Scheduler / Timer	True
Remote Management	True
Gain Control	True
SNMP	True

Audio settings with equalizer, CEC Support, Colour temperature mode, Display Browser Control, Energy saving picture mode, HDMI with UHD at 60 Hz, Powered USB-Port, PLink Support, Retail picture mode, Scheduler, SNMP Support, HDMI ARC, User input priority definition

Power Consumption (W) (Operating MAX)	85
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	5
Storage Humidity [%]	85

RS232C IN	1
LAN Port	1
USB	1

Colour Versions	Black Front Bezel, Black Back Cabinet
-----------------	---------------------------------------

Operating Humidity (min) [%]	10
Operating Humidity (max) [%]	80

Product Weight Without Stand (Kg)	5
-----------------------------------	---

