

Digital Signage

PN-HY501



With the PN-HY501, you can enjoy the perfect combination of an elegant design and crystal clear pictures whether it's a meeting room, reception area or other retail environments.

- Make an impact with the 50 display in your retail or corporate environments
- Showcase images and video in detail with 4K Ultra HD resolution (3840 x 2160 pixels)
- Enhanced and true representation of colour shown from wide colour gamut
- Continuous display of content during business operating hours 24/7
- Show and hear content easily with integrated 4K USB media player and speakers
- Latest HDMI Connectivity for 4K at 60Hz
- Slim, sleek and elegant design to suit any setting
- Flexible installation in portrait and landscape

Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Operation Manual, Installation Set- Up Manual, CD Rom, Power Cord, Battery, Cable Clamp, Portrait Mount Sticker Kit
Panel Technology	TFT-LCD
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Backlight Technology	W-LED / Full Array
Brightness (cd/m2)	500
Contrast Ratio	4000:1
Display Colours	1060
Response Time (grey to grey avg) ms	8
Pixel Pitch (mm H/V)	0,285
Viewing Angle [°]	178
Active Screen Area (H/V) mm	1095 x 616
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Standby)	50
Operating Temperature (oC)	0 - 40
HDMI	3
Audio 3.5mm Jack	1
VGA	1
Bezel Size (L/R) mm	15
Bezel Size (U) mm	15
Bezel Size (L) mm	15
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Product Weight Without Stand (Kg)	15

24/7 Operation Certified	True
Built in Speakers (W)	10 + 10
Computer Input - Plug and Play	True
Power Management	True
Cabinet Colour	Black
Fanless	True
Temperature Sensor	True
Residual Image Reduction Feature	True
Multi-Screen Function - Videowall Mode (Enlarge Feature)	True
Multi Language OSD	True
Remote Management	True
Adjustment Lock Feature	True
Displaying Use Time Feature	True
Screen Adjustment	True
Colour Temperature Adjustment	True
Gamma Adjustment	True
Self-Adjust	True
Hardware Diagnosis	True
Monitor Control Software Support	True
Temperature Control	True

Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 400
Mounting Screw Specification (Size/Max Length)	M6

RS232C IN	1
LAN Port	1
USB	1

Diagonal Size (inches / cm)	50
Diagonal Size (inches / cm)	125

Audio RCA R-L	1
---------------	---

CE, CB Report	True
---------------	------



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: PN-HY501_30/6/2026