

Digital Signage

NEC MULTISYNC E658



De funktioner, du har brug for, til den pris, du ønsker.

- Reducerede installations- og driftsomkostninger – et yderst energieffektivt display med LED-baggrundsbelysning sikrer et lavere strømforbrug, baggrundsbelysning med en længere levetid og et lettere de
- Slankt design og indbyggede højttalere – det æstetiske design ser flot ud og muliggør nem og billig installation.
- Nem afspilning af indhold - den integrerede USB-medieafspiller understøtter forskellige billedvideofilformater for at sikre nem og alenestående afspilning af indhold.
- Fremtidssikrede forbindelsesmuligheder – udstyret med flere digitale og analoge signalindgange, der opfylder industristandarderne, for at sikre fleksibel integration i AV-infrastrukturer.
- Alenestående drift – displayet er designet til enkel, alenestående drift takket være integreret USB-medieafspiller, højttalere og planlægningsfunktion.

Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, HDMI Cable, Mounting Bracket, Tabletop Stand, Trolley Stand
Shipping Content	2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Backlight Technology	Direct LED
Brightness (cd/m2)	350
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Pixel Pitch (mm H/V)	0,372
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Active Screen Area (H/V) mm	1428.48 x 803.52

Component	1
Composite	1
HDMI	3
Audio 3.5mm Jack	1
VGA	1

RS232C IN	1
LAN Port	1
USB	1

Diagonal Size (inches / cm)	65
Diagonal Size (inches / cm)	164

Bezel Size (L/R) mm	13
Bezel Size (U) mm	14

Product Weight Without Stand (Kg)	24
-----------------------------------	----

[AVSpecificationConnectivityOutputAudio35MmJack]1

Special Characteristics

HDR High Dynamic Range	Yes
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10 + 10
Cabinet Colour	Black
Temperature Sensor	True
Brightness Sensor	True
Scheduler / Timer	True

Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	225
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	5
Storage Humidity [%]	85

Landscape	True
Mounting (VESA/Number of Points/Pitch mm)	600 x 400 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6

Colour Versions	Black Front Bezel, Black Back Cabinet
-----------------	---------------------------------------

Operating Humidity (min) [%]	10
Operating Humidity (max) [%]	80

Energy Star	True
-------------	------

Haze Level [%]	1
----------------	---

