



- ▶ ELEGANT SLIM CABINET / BEZEL DESIGN
- ▶ SHARP PROPRIETARY UV2A TFT PANEL
- ▶ HIGH CONTRAST RATIO OF 4000:1 FOR CHRYSTAL CLEAR PICTURE RENDITION
- ▶ DEVELOPED FOR PROFESSIONAL 24/7 APPLICATION
- ▶ DESIGNED FOR PROLONGED PORTRAIT AND LANDSCAPE INSTALLATION
- ▶ ENERGY EFFECIENT LED BACKLIGHT
- ▶ COMPREHENSIVE SET OF SIGNAL INPUT INTERFACE
- ▶ FULL LAN AND RS232 REMOTE CONTROLLABILITY

This 60" Sharp display combines full-HD image quality, a stylishly thin profile, and energy efficiency to create an appealing professional signage solution for a wide range of applications. With its sleek design, round-the-clock operation, and support for landscape and portrait installations, this display offers an amazing degree of flexibility. In hotel lobbies, conference rooms, retail spaces, and elsewhere, the PN-E603 will grab and keep the attention of your target audience.

DISPLAY MODULE DATA

- Panel Technology: **UV2A LCD**
- Native Resolution (Pixels): **1920 x 1080**
- Diagonal Size (inches / cm): **60/152.5**
- Aspect Ratio: **16:9**
- Backlight Technology: **W-LED edge lit**
- Brightness (cd/m²): **450**
- Contrast Ratio: **4000:1**
- Display Colours: **1.06B**
- Viewing Angle (H/V) CR >10: **176/176**

KEY SPECIFICATIONS

- 24/7 Operation Certified: **✓**
- Built in Speakers (W): **10 + 10**
- Computer Input - Plug and Play: **✓**
- Power Management: **✓**
- Cabinet Colour: **Black**
- Fanless: **✓**
- Multi-Screen Function - Videowall Mode (Enlarge Feature): **✓**
- Daisychain (Mirror mode): **✓**
- Hardware Diagnosis: **✓**
- Monitor Control Software Support: **✓**

POWER SUPPLY AND OPERATING ENVIRONMENT

- Operating Voltage(ACV) / Frequency(Hz): **100 - 240/50 - 60**
- Power Consumption (W) (Operating MAX): **180**
- Operating Temperature (°C): **0 to 40**
- Humidity (%): **20 to 80**
- Heat Dissipation (BTU/h) MAX: **597**

WEIGHTS AND MEASURES

- Bezel Size (L/R) mm: **19/19**
- Bezel Size (U/L) mm: **19/19**
- Product Dimensions (W/H/D) mm: **1,378/794/39.4**
- Product Weight Without Stand (Kg): **32**

CONNECTIVITY (AUDIO/VIDEO) INPUT

- HDMI: **2**
- DVI-I: **1**
- DisplayPort: **1**
- VGA: **1**
- Audio 3.5mm Jack: **1**

CONNECTIVITY (CONTROL/SERIAL DATA)

- RS232C IN: **1**
- RS232C OUT: **1**
- LAN Port: **1**
- Other: **USB (for service)**

SAFETY AND ENVIRONMENT (EUROPE)

- CE, CB Report: **✓**
- Mercury Content (mg): **0**
- Presence of Lead (Accepted application of RoHS Directive): **✓**

INSTALLATION

- Landscape: **✓**
- Portrait: **✓**
- Mounting (VESA/Number of Points/Pitch mm): **6/200mm x 200mm or 4/200mm x 200mm**

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

- DVI-D: **1**
- DisplayPort: **1**
- Audio/Headphone 3.5mm Jack: **1**

ACCESSORIES

- Other: **1 pc. Logo label for portrait mounting**