

Big Pad Interaktive displays

# NEC MULTISYNC WD551



- Bring your own meeting (BYOM) – en enkel, samlet løsning til øjeblikkelig start af møder ved hjælp af hvilken som helst enhed.
- Forbindelse uden problemer og besvær – et enkelt, sikkert USB-C-kabel forbinder din enhed med displayet for automatisk synkronisering af det indbyggede kamera, højttalerne, mikrofonen, touchskærm og p
- Certificeret til Microsoft Teams og mere – en problemfri BYOM-løsning kører videomøder via din foretrukne konferenceplatform.
- Naturlig touch-fornemmelse, nem at gøre ren – det rengøringsvenlige, flugtende skærmdesign reducerer parallakse og giver en fantastisk skriveoplevelse, idet det understøtter Windows Ink med to inkluderede
- Smart styring af rum – opnå maksimal komfort i dine møderum, og oprethold optimale miljømæssige parametre, idet du bruger de indbyggede IoT-sensorer til at administrere analyserne i alle dine mødeloka

# Specifikationer

## Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, USB Cable, Stylus, Mounting Bracket, Trolley Stand, Cable Clamp
Shipping Content	2 x AAA batteries, 2 x Passive Stylus, Cable Clamps, Display, Remote Control, Pen Tray, Power Cable, Setup Manual, USB cable
Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Screen Filter	AG
Backlight Technology	LED
Brightness (cd/m2)	400
Contrast Ratio	1200:1
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Active Screen Area (H/V) mm	1209.6 x 680.4
Response Time (typ.) [ms]	8
Power Consumption (W) (Operating MAX)	371
Operating Temperature (oC)	0 - 40
Storage Humidity [%]	10
Storage Humidity [%]	90
RS232C IN	1
LAN Port	1
USB	2
HDMI	1
[AVSpecificationConnectivityInputUsbc]	2
Energy Star	True
WLAN	True
[AVSpecificationResolution]	Output HD 3840p 30fps

Number of Touch Points	20
Safety Glass Thickness (mm)	3
Pen Mode / Finger Mode	True
Screen Hardness (H)	7
Operating System Compatibility	Android, Linux, Windows, Mac OSX
Light Transmission [%]	≥ 88
Reflection Rate [%]	4
Touch Method	Active Stylus, Conductive Passive Stylus (≥ 8 mm), Finger
Data Interface	USB-HID
Windows Ink	True
[AVSpecificationTechnology]	Projected Capacitive Touch (P-CAP)
Special Characteristics	Microsoft Teams Certified, AMX NetLinX Support
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	12 + 12
Option Slot Interface	True
Cabinet Colour	Black
Temperature Sensor	True
Brightness Sensor	True
IP Rating	True
Operating Time	16/7
Landscape	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 200 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M8
[AVSpecificationArray]	6
[AVSpecificationDistanceM]	6
[AVSpecificationDegrees]	180
Diagonal Size (inches / cm)	55
Diagonal Size (inches / cm)	139
Product Weight Without Stand (Kg)	31
Light Sensor Processing	-

