

Digital Signage

SHARP MULTISYNC® M322 LCD 32" MESSAGE LARGE FORMAT DISPLAY



Til omkostningseffektiv digital skiltning i 24/7 miljøer leverer 32" Sharp MultiSync® M322 professionel ydeevne og den funktionalitet, der kræves til digital signage, samtidig som den minimerer de samlede ejeromkostninger.

- Moderne og slankt design – robust, men elegant, så skærmen nemt kan integreres diskret i alle miljøer og applikationer.
- Sikker fjernstyring – administrer dine enheder sikkert og på afstand med NEC NaviSet Administrator 2; overvåg og håndter servicebehov proaktivt for at spare tid og ressourcer.
- Optimal læsbarhed – et high haze panel reducerer blænding fra vinduer og omgivende lys, så skiltindhold og præsentationer er tydelige og letlæselige i alle miljøer.
- Klar til mission kritisk 24/7 drift – robuste industrikomponenter og en gennemtænkt konstruktion sikrer stabil og pålidelig drift døgnet rundt i krævende miljøer.
- Fremtidssikker tilslutning – udstyret med flere digitale og analoge standardindgange for fleksibel integration i AV miljøer.

Specifikationer

Bezel Size (L/R) mm	12
Bezel Size (U/L) mm	12
Response Time (grey to grey avg) ms	8
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Via AC Adapter	True
Operating Voltage(DCV)	100-240
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	90
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
[AVSpecificationBattery]	< 0.5 (ECO Standby)
Panel Technology	VA with Direct LED backlights
Native Resolution (Pixels)	1920 x 1080
Aspect Ratio	16:9
Brightness (cd/m2)	450
Contrast Ratio	4000:1
Viewing Angle [°]	178
Colour Depth [bn]	16.7 (8bit)
Response Time (typ.) [ms]	8
Supported Resolution	1024 x 768 , 1920 x 1200, 1400 x 1050, 1366 x 768, 1280 x 768, 3840 x 2160, 4096 x 2160, 1280 x 720, 2560 x 1440, 1920 x 1080, 1600 x 1200, 1280 x 1024, 1440 x 900
Shipping Carton Dimensions (W/H/D) mm	870
Shipping Carton Dimensions (W/H/D) mm	527
Shipping Carton Dimensions (W/H/D) mm	160
Shipping Weight (Kg)	10
Diagonal Size (inches / cm)	32
Diagonal Size (inches / cm)	80
Colour Gamuts	72% NTSC
Digital	DisplayPort, HDMI, USB Type C
Analog	VGA
Output Control	LAN 100Mbit
[AVSpecificationLandscapeDimensionsWidthMm]	727
[AVSpecificationLandscapeDimensionsHeightMm]	426
[AVSpecificationLandscapeDimensionsDepthMm]	67
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
[AVSpecificationWeightKg]	6

Special Characteristics	DICOM Simulation, HDMI ARC, Powered USB Port (10 W), Removable Logo
24/7 Operation Certified	True
Built in Speakers (W)	5 + 5
Power Management	True
Temperature Sensor	True
Remote Management	True
Operating Time	24/7
[AVSpecificationSupportedImageFormats]	Max. resolution 15360 x 8640, JPG (baseline, progressive, RGB, CMYK)
Portrait	True
Landscape	True
Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	200 x 200 (FDMI), 100 x 100 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M4
[AVSpecificationFaceUp]	True
Colour Versions	Black Front Bezel
Safety & Ergonomics	RoHS, ISO 9241-307 (pixel failure class 2), CE, EAC
Limited Manufacturer's Warranty (yrs.)	Optional 4th to 5th year warranty extension, [additional-services-available], 3 years warranty incl. backlight
Accessories	
[AVSpecificationAccessories]	[feet], [presence-sensor], [wall-mount]
Shipping Content	Power Cable, Remote Control, HDMI Cable, 2 x AAA batteries, Setup Manual, Display
Energy Efficiency	LED backlight technology, Energy consumption: 41 kWh/1000 h, Energy efficiency class: G
Ecological Standards	Energy Star 8.0
Bezel Size (L/R) mm	12
Bezel Size (U) mm	12
Bezel Size (L) mm	17
Horizontal Frequency [kHz]	26 - 91.1
Vertical Frequency [Hz]	23 - 86
Power Consumption on-mode (IEC62087:2012)	40 (shipping)
Power Supply	100-240 V
Haze Level [%]	Pro 28

