

Desktop Display

MultiSync E224F



- Omkostnings- og tidsbesparende drift – baseret på et intuitivt OSD-design, der gør opsætningen enklere.
- Sort og hvid farveversioner – hvid anses at reducere indtrykket af tunnelsyn, når den placeres foran en hvid baggrund, såsom kontorvægge.
- Bedst i form og funktion – fremtidssikker design med 3-sidet ultratynd ramme, tilgængelig i sort eller hvid, som supplerer en frisk professionel kontorindretning.
- Ergonomic – full height adjustability (120 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.
- Sikring af brugerens velvære – indbygget Low Blue Light-teknologi filtrerer farlige blå lysudslip, mens Flicker-Free-teknologi eliminerer baggrundsbelysningens flimmer, hvilket beskytter brugernes øjn

Specifications

DISPLAY

Panel Technology	VA TFT with W-LED backlight
Screen Size [inch/cm]	22 / 55
Pixel Pitch [mm]	0.249
Brightness (typ.) [cd/m²]	250
Contrast Ratio (typ.)	3000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	6
Colours [Mio.]	16.77
Screen Aspect Ratio	16:9

RESOLUTION

Optimum Resolution	1920 x 1080 at 60 Hz
--------------------	----------------------

ELECTRICAL

Power Consumption on Mode [W]	10 (Eco Mode 2); 14 (typ.)
Power Savings Mode [W]	0.22
Power Supply	integrated power supply

ERGONOMICS

Screen Tilt [°]	-5 to 25
Height adjustable stand [mm]	120
Screen Swivel [°]	170 to -170
Screen Rotate [°]	-90 to 90 (landscape to portrait mode)

MECHANICAL

Bezel Width [mm]	16.8 (bottom); 2.5 (left / right / top)
Dimensions (W x H x D) [mm]	493.2 x 363.4 - 483.4 x 233.2 (Landscape mode)
Weight [kg]	With stand: 5.2; Without stand: 3.1
VESA Mounting [mm]	100 x 100

SYNCHRONISATION RATE

Vertical Frequency [Hz]	50 - 75
-------------------------	---------

CONNECTIVITY

Digital	1 x DisplayPort; 1 x HDMI
Analog	1 x D-sub 15 pin

ENVIRONMENTAL CONDITIONS

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 85
Storage Temperature [°C]	-10 to 60

ADDITIONAL FEATURES

Special Characteristics	Flicker Free; Low Blue Light
Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
Cable Management	•
Kensington security slot	•
Plug and Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable); Headphone Jack
Shipping Content	DisplayPort Cable; Power Cable; Setup Guide
Safety and Ergonomics	EnergyStar 8.0; Flicker-free; ISO 9241-307 (pixel failure class I); Low Blue Light; RoHS; TCO 9.0; TÜV Ergonomics; TÜV GS; WEEE
Warranty	3 years warranty incl. backlight
GREEN FEATURES	
Energy Efficiency	Carbon footprint meter / Carbon savings meter; ECOMode
Ecological Standards	RoHS compliant

