

NEC MultiSync ME651



- Moderne og slankt design – robust, men elegant, mulighed for diskret integration i hvilken som helst anvendelse og alle miljøer.
- Brugervenlig betjening og drift – smarte installations-, drifts- og vedligeholdelsesfunktioner sikrer præcise præstationer i hele displayets levetid samt besparelser af tid, anstrengelser og ressource
- Nem afspilning af indhold - den integrerede USB-mediaafspiller understøtter forskellige billedvideofilformater for at sikre nem og alenestående afspilning af indhold.
- Sikker fjernstyring – styr dine enheder sikkert på afstand ved hjælp af NEC NaviSet Administrator 2. Administrér vedligeholdelsesbehovene proaktivt, og spar tid og ressourcer.
- Fremtidssikrede forbindelsesmuligheder – udstyret med flere digitale og analoge signalindgange, der opfylder industristandarderne, for at sikre fleksibel integration i AV-infrastruktur.

Specifikationer

DISPLAY MODULE DATA

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Diagonal Size (inches / cm)	65 / 163.9
Aspect Ratio	16:9
Brightness (cd/m2)	400
Contrast Ratio	≥ 8000:1
Response Time (grey to grey avg) ms	6
Viewing Angle (H/V) 0 CR >10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Colour Depth [bn]	1.073 (8bit + FRC)
Haze Level [%]	1

POWER SUPPLY AND OPERATING ENVIRONMENT

Operating Voltage(ACV) / Frequency(Hz)	100-240 V AC; 50 / 60 Hz
Power Consumption (W) (Operating MAX)	165 shipping
Operating Temperature (oC)	0 to 40
Storage Temperature [°C]	-20 to 60
Humidity (%)	20 to 80
Storage Humidity [%]	10 to 90

INSTALLATION

Landscape	•
Portrait	•
Mounting (VESA/Number of Points/Pitch mm)	4; 400 x 400 (FDMI)

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

Audio/Headphone 3.5mm Jack	1
----------------------------	---

ACCESSORIES

Shipping Content	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
Remote Control Transmitter	Yes
Power Cord	Yes
Mounting Bracket	Optional
Tabletop Stand	Optional

KEY SPECIFICATIONS

Special Characteristics	DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo
HDR High Dynamic Range	Yes
Limited Manufacturer's Warranty (yrs.)	3
Local Dimming	•
Built in Speakers (W)	10 W + 10 W
Power Management	•
Cabinet Colour	Black
Temperature Sensor	•

WEIGHTS AND MEASURES

Bezel Size (L/R) mm	14.9
Bezel Size (U/L) mm	14.9
Product Dimensions (W/H/D) mm	1,462.3 x 837.3 x 68.1
Shipping Carton Dimensions (W/H/D) mm	1,736 x 1,033 x 280
Product Weight Without Stand (Kg)	29.4
Shipping Weight (Kg)	41.7

CONNECTIVITY (AUDIO/VIDEO) INPUT

HDMI	2
DisplayPort	1
Audio 3.5mm Jack	1

CONNECTIVITY (CONTROL/SERIAL DATA)

RS232C IN	1
LAN Port	1
USB	1

