

Big Pad Interaktive displays

SHARP/ NEC MULTISYNC® M751 IGB

Understøt interaktive sessioner i lyse og moderne mødelokaler med Sharp/NEC MultiSync® M751 IGB, hvis InGlass™-berøringsteknologi giver problemfri interaktiv berøringsydelse.

- Klassens bedste visuelle ydeevne – drage fordel af en pixelfri visuel ydeevne i Ultra-High Definition (UHD).
- Naturlig skriveoplevelse – Uanset om du bruger finger eller pen, giver InGlass™-berøringsteknologien sømløs interaktiv berøringsydeevne, inklusive Windows Ink og håndfladeafvisning.
- NEC Open Modular Intelligence (OMI) slot-in-teknologi – vælg skalerbar computerkraft med Raspberry Pi Compute Module 4 eller Intel® Smart Display Modules (Intel®SDM) til skræddersyede løsninger.
- Missionskritisk 24/7 klar drift – valget af komponenter i industriel kvalitet og omhyggeligt design fokuseret på krævende brugsscenarier ledsager en imponerende og kontinuerlig seeroplevelse.
- Bliv mere produktiv – få et års gratis licens til FlatFrog Board for Rooms! FlatFrog Board whiteboard-software gør hybrid arbejde nemt og lige produktivt for alle.

Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, USB Cable, HDMI Cable, Stylus, Battery
Shipping Content	2 x Passive Stylus, 2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual, USB cable
Number of Touch Points	20
Pen Mode / Finger Mode	True
Screen Hardness (H)	7
Operating System Compatibility	Native Multi-Touch, Windows 7, Windows 8, Windows 10, Linux, Android, Default Mouse, Windows XP, Windows Vista, Mac OSX Pro 25
Haze Level [%]	3
Thickness [mm]	3
Touch Method	Finger, Gloves, Stylus (≥ 2 mm)
Data Interface	USB-HID
Accuracy [mm]	1
Palm Rejection	True
Windows Ink	True
[AVSpecificationTechnology]	InGlass™
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	205
Operating Temperature (oC)	0 - 35
Storage Humidity [%]	20
Storage Humidity [%]	80
Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	600 x 400
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M8
RS232C IN	1
LAN Port	2
USB	3
Bezel Size (L/R) mm	22
Bezel Size (U) mm	22
Light Sensor Processing	-

Special Characteristics	Frame Comp, Powered USB Port (10 W), Removable Logo
24/7 Operation Certified	True
Limited Manufacturer's Warranty (yrs.)	3
Local Dimming	True
Built in Speakers (W)	10 + 10
Power Management	True
Equipment Space (Mounting)	True
Temperature Sensor	True
Picture in Picture Mode	True
Scheduler / Timer	True
Remote Management	True
E-Mail Notification	True
SNMP	True
Internal/External Speaker Selection	True
Operating Time	24/7
Panel Technology	ADS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Screen Filter	AG
Backlight Technology	LED
Brightness (cd/m2)	500
Contrast Ratio	8000:1
Response Time (grey to grey avg) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Shipping Carton Dimensions (W/H/D) mm	1830
Shipping Carton Dimensions (W/H/D) mm	1070
Shipping Carton Dimensions (W/H/D) mm	225
Product Weight Without Stand (Kg)	62
Shipping Weight (Kg)	76
DisplayPort	3
HDMI	4
Audio 3.5mm Jack	1
DisplayPort	1
HDMI	1
[AVSpecificationConnectivityOutputAudio35MmJack]	1
Diagonal Size (inches / cm)	75
Diagonal Size (inches / cm)	189
CE, CB Report	True

