


Digital Signage

Sharp/ NEC MultiSync ME502



For enestående ydeevne i mødelokaler og digitale skilteløsninger tilbyder ME-serien klassens bedste visuelle ydeevne og værdi for at understøtte dine behov.

- Problemfri tilslutning – indbygget USB-C understøtter Bring Your Own Device-workflows, der sikrer inklusion og øger produktiviteten med en enkelt kabelforbindelse mellem notebook og skærm.
- Bedste læsbarhed – og hjælper med høj produktivitet i veloplyste mødelokaler, et filter med høj uklarhed eliminerer blænding og refleksioner fra vinduer og andre lyskilder.
- Hurtig inputdetektion – fjerner potentiel frustration og udjævner vejen til produktive møderesultater, skærmen reagerer med det samme, når en enhed er tilsluttet.
- Tredjepartskompatibilitet – ikke blot en skærm, men en klar løsning, der er kompatibel med populære arbejdsplads- og indholdsstyringsystemer via den integrerede SoC-platform.
- Ny funktion klar – regelmæssige OTA Android OS-opdateringer sikrer tilgængeligheden af de nyeste funktioner og systemsikkerhed.

Specifikationer

Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Installation Set-Up Manual, Power Cord, HDMI Cable, Mounting Bracket, Tabletop Stand, Trolley Stand, Battery
Shipping Content	2 x AAA batteries, Display, HDMI Cable, Power Cable, Remote Control, Setup Manual
Special Characteristics	Frame Comp, Powered USB Port (10 W), Powered USB Port (5 W), Powered USB Port (15 W)
Limited Manufacturer's Warranty (yrs.)	3
Built in Speakers (W)	10 + 10
Power Management	True
Equipment Space (Mounting)	True
Cabinet Colour	Black
Scheduler / Timer	True
Landscape	True
Portrait	True
Mounting (VESA/Number of Points/Pitch mm)	400 x 400 (FDMI)
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M6
RS232C IN	1
LAN Port	1
USB	4
Diagonal Size (inches / cm)	50
Diagonal Size (inches / cm)	126
Bezel Size (L/R) mm	10
Bezel Size (U) mm	10
Haze Level [%]	Pro 25

Panel Technology	VA with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Backlight Technology	LED
Brightness (cd/m2)	450
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	6
Viewing Angle [°]	178
Colour Depth [bn]	1073 (8bit + FRC)

Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	85
Operating Temperature (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	90

Shipping Carton Dimensions (W/H/D) mm	1202
Shipping Carton Dimensions (W/H/D) mm	719
Shipping Carton Dimensions (W/H/D) mm	156
Product Weight Without Stand (Kg)	12
Shipping Weight (Kg)	18

HDMI	0
[AVSpecificationConnectivityOutputAudio35MmJack]	1
Audio/Headphone 3.5mm Jack	1

HDMI	3
Audio 3.5mm Jack	1

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Energy Star	True
-------------	------