

This is Why



- 70" (176.6 CM) DIAGONAL SCREEN SIZE
- 1.920 X 1.080 RESOLUTION IN DOTS
- UV2A TECHNOLOGY
- CONTRAST 4.000:1
- LED, EDGE LIT
- 24 / 7 OPERATION
- ENERGY EFFICIENT

Ample sized and attractively designed, Sharp's PN-R703 professional LCD monitors have the thin profile, high brightness, and low power consumption to accomodate a wide range of indoor digital signage applications. Exceptionally thin and lightweight, this streamlined monitor makes for easy, eye-pleasing installations and can be counted on for reliable, energy-efficient operation. Thanks to the Edge-lit LED backlighting on the PN-R703; this monitor consumes roughly only 32.5/50% which is less energy than the conventional CCFL-backlight displays.

DISPLAY MODULE DATA

- Panel Technology: **LCD UV2A RGB**
- Native Resolution (Pixels): **1920 X 1080**
- Diagonal Size (inches / cm): **70/176.6**
- Aspect Ratio: **16:9**
- Backlight Technology: **EDGE LIT LED**
- Brightness (cd/m²): **700**
- Contrast Ratio: **4000 : 1**
- Display Colours: **1.06b**
- Response Time (grey to grey avg) ms: **6**
- Viewing Angle (H/V)0 CR >10: **176 x 176**

KEY SPECIFICATIONS

- 24/7 Operation Certified: **✓**
- Built in Speakers (W): **10 x 10**
- Computer Input - Plug and Play: **✓**
- Power Management: **✓**
- Cabinet Colour: **BLACK**
- Fanless: **✓**
- Multi-Screen Function - Videowall Mode (Enlarge Feature): **✓**
- Daisychain (Mirror mode): **✓**
- Hardware Diagnosis: **✓**
- Monitor Control Software Support: **✓**

POWER SUPPLY AND OPERATING ENVIRONMENT

- Operating Voltage(ACV) / Frequency(Hz): **100 - 240/50-60**
- Power Consumption (W) (Operating MAX): **270**
- Power Consumption (W) (Standby): **0.5**
- Operating Temperature (oC): **0 - 40**
- Humidity (%): **20 - 80**

WEIGHTS AND MEASURES

- Bezel Size (L/R) mm: **18**
- Bezel Size (U/L) mm: **19**
- Product Dimensions (W/H/D) mm: **1578 x 916 x 39.4**
- Product Weight Without Stand (Kg): **43**

CONNECTIVITY (AUDIO/VIDEO) INPUT

- HDMI: **2**
- DVI-I: **1**
- DisplayPort: **1**
- VGA: **1**
- Component: **1**
- Composite: **1**
- Audio 3.5mm Jack: **2**

CONNECTIVITY (CONTROL/SERIAL DATA)

- RS232C IN: **1**
- RS232C OUT: **1**
- LAN Port: **1**

SAFETY AND ENVIRONMENT (EUROPE)

- CE, CB Report: **✓**
- Mercury Content (mg): **0**

INSTALLATION

- Landscape: **✓**
- Portrait: **✓**
- Mounting (VESA/Number of Points/Pitch mm): **6/200mm x 200mm or 4/200mm x 200mm**

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

- DVI-D: **1**
- DisplayPort: **1**
- Audio/Headphone 3.5mm Jack: **1**