


Big Pad Interaktive displays

# SHARP/ NEC PN-LA652



PN-LA-serien, der integreres elegant og problemfrit i avancerede mødelokaler og bestyrelseslokaler, opretholder de højeste IT-sikkerhedsstandarder, samtidig med at den tilbyder fleksibilitet og understøtter maksimal produktivitet.

- Mest naturlige skriveoplevelse – InGlass™ M5 premium touch-system understøtter patenteret trykfølsomhed ved hjælp af passive penne samt Windows Ink og håndfladeafvisning.
- Sikker ved design – ikke-Android-plattformen med yderligere sikkerhedsfunktioner opfylder de højeste it-sikkerhedsstandarder.
- Valgfri Windows-baseret Intel SDM-slot-in-pc – giver ubegrænset alsidighed med kraftfuld integreret databehandling for hurtig og nem adgang til dine apps, der tilbyder et sikkert og låst miljø.
- Forøg din produktivitet – drag fordel af en gratis etårig licens til FlatFrog Board for Rooms. FlatFrog Board whiteboard-software gør hybrid arbejde nemt og produktivt for alle
- Energieffektivitet – indbygget funktionalitet inklusive en omgivende lyssensor, registrering af menneskelig tilstedeværelse og øko-tilstande hjælper med at reducere strømforbruget.

# Specifikationer

## Accessories

[AVSpecificationAccessories]	Remote Control Transmitter, Operation Manual, Power Cord, USB Cable, Stylus, Battery, Cable Clamp
Shipping Content	1 x 300 cm USB Cable, 2 x Passive Stylus, 2 x AAA batteries, Blank Sticker, Bracket for Camera, Bracket for Mini PC, Cable Clamps, Display, Power Cable, Remote Control, Setup Manual
Number of Touch Points	20
Pen Mode / Finger Mode	True
Screen Hardness (H)	8
Operating System Compatibility	Native Multi-Touch, Windows 7, Windows 8, Windows 10, Linux, Android, Default Mouse, Windows XP, Windows Vista, Mac OSX
Thickness [mm]	3
Touch Method	Finger, Gloves, Stylus (≥ 2 mm)
Data Interface	USB-HID
Accuracy [mm]	1
Palm Rejection	True
Windows Ink	True
[AVSpecificationTechnology]	InGlass™ M5
Operating Voltage(ACV) / Frequency(Hz)	100-240
Operating Voltage(ACV) / Frequency(Hz)	50-60
Power Consumption (W) (Operating MAX)	190
Operating Temperature (oC)	5 - 35
Storage Humidity [%]	20
Storage Humidity [%]	80
Shipping Carton Dimensions (W/H/D) mm	1660
Shipping Carton Dimensions (W/H/D) mm	1010
Shipping Carton Dimensions (W/H/D) mm	220
Product Weight Without Stand (Kg)	49
Shipping Weight (Kg)	59
Bezel Size (L/R) mm	5
Bezel Size (U) mm	5
Bezel Size (L) mm	32
Diagonal Size (inches / cm)	65
Diagonal Size (inches / cm)	164
Light Sensor Processing	-

Special Characteristics	Frame Comp, Powered USB Port (10 W), Advanced NTAA
24/7 Operation Certified	True
Limited Manufacturer's Warranty (yrs.)	3
Local Dimming	True
Built in Speakers (W)	10 + 10
Cabinet Colour	Black
Temperature Sensor	True
Brightness Sensor	True
Picture in Picture Mode	True
Picture by Picture Mode	True
Scheduler / Timer	True
Remote Management	True
E-Mail Notification	True
SNMP	True
Operating Time	24/7

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Screen Filter	AG
Backlight Technology	LED
Brightness (cd/m2)	450
Contrast Ratio	1200:1
Response Time (grey to grey avg) ms	8
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)

Landscape	True
Portrait	True
Horizontal	True
Mounting (VESA/Number of Points/Pitch mm)	600 x 400
Mounting (VESA/Number of Points/Pitch mm)	4
Mounting Screw Specification (Size/Max Length)	M8

DisplayPort	1
HDMI	2
[AVSpecificationConnectivityInputUsbc]	1

RS232C IN	1
LAN Port	1
USB	4

DisplayPort	1
[AVSpecificationConnectivityOutputAudio35MmJack]	1

CE, CB Report	True
---------------	------

