

# NEC MultiSync MA551



- Uhindret læsbarhed – ingen genspejling fra vinduer eller andre lyskilder betyder, at skiltens indhold eller præsentationen i mødelokalet hele tiden er synlige.
- Sikker på offentlige steder – takket være en metalafdækning bagtil og intelligent varmestyring er den sikker at anvende på offentlige steder, hvor der er krav om brandbeskyttelse.
- Missionskritisk, klar til drift 24/7 – valget af industrielle komponenter og omhyggeligt design fokuseret på svære anvendelsesscenarier går hånd i hånd med en imponerende og uafbrudt brugeroplevelse.
- Stort farveområde – den højtydende panelteknologi leverer et bredt udvalg af farver for at sikre en udsøgt visuel oplevelse.
- Forbedret visning af billeder - avancerede indstillinger af relevante, visuelle parametre giver mulighed for fuld kontrol af lysstyrke, farve, gamma og ensartethed via SpectraView Engine for præcise,

# Specifikationer

## DISPLAY MODULE DATA

|                                     |                                                             |
|-------------------------------------|-------------------------------------------------------------|
| Panel Technology                    | IPS with Edge LED backlights                                |
| Native Resolution (Pixels)          | 3840 x 2160                                                 |
| Diagonal Size (inches / cm)         | 55 / 138.8                                                  |
| Aspect Ratio                        | 16:9                                                        |
| Brightness (cd/m2)                  | 500                                                         |
| Contrast Ratio                      | ≥ 8000:1                                                    |
| Response Time (grey to grey avg) ms | 8                                                           |
| Viewing Angle (H/V) @ CR > 10       | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Colour Depth [bn]                   | 1.073 (10bit)                                               |
| Haze Level [%]                      | 28                                                          |

## POWER SUPPLY AND OPERATING ENVIRONMENT

|                                        |                          |
|----------------------------------------|--------------------------|
| Operating Voltage(ACV) / Frequency(Hz) | 100-240 V AC; 50 / 60 Hz |
| Power Consumption (W) (Operating MAX)  | 90 shipping              |
| Operating Temperature (oC)             | 0 to 40                  |
| Storage Temperature [°C]               | -20 to 60                |
| Humidity (%)                           | 20 to 80                 |
| Storage Humidity [%]                   | 10 to 90                 |

## INSTALLATION

|                                           |                     |
|-------------------------------------------|---------------------|
| Landscape                                 | •                   |
| Portrait                                  | •                   |
| Horizontal                                | •                   |
| Mounting (VESA/Number of Points/Pitch mm) | 4; 300 x 300 (FDMI) |

## CONNECTIVITY (AUDIO/VIDEO) OUTPUT

|                            |   |
|----------------------------|---|
| HDMI                       | 1 |
| DisplayPort                | 1 |
| Audio/Headphone 3.5mm Jack | 1 |

## ACCESSORIES

|                            |                                                                                  |
|----------------------------|----------------------------------------------------------------------------------|
| Shipping Content           | 2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual |
| Remote Control Transmitter | Yes                                                                              |
| Power Cord                 | Yes                                                                              |
| Mounting Bracket           | Optional                                                                         |
| Tabletop Stand             | Optional                                                                         |

## KEY SPECIFICATIONS

|                                        |                                                                     |
|----------------------------------------|---------------------------------------------------------------------|
| Special Characteristics                | DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo |
| 24/7 Operation Certified               | •                                                                   |
| Limited Manufacturer's Warranty (yrs.) | 3                                                                   |
| Local Dimming                          | •                                                                   |
| Power Management                       | •                                                                   |
| Cabinet Colour                         | Black                                                               |
| Temperature Sensor                     | •                                                                   |
| Brightness Sensor                      | •                                                                   |

## WEIGHTS AND MEASURES

|                                       |                      |
|---------------------------------------|----------------------|
| Bezel Size (L/R) mm                   | 12.5                 |
| Bezel Size (U/L) mm                   | 12 / 15.6            |
| Product Dimensions (W/H/D) mm         | 1,239.6 x 713 x 61.1 |
| Shipping Carton Dimensions (W/H/D) mm | 1,430 x 920 x 250    |
| Product Weight Without Stand (Kg)     | 27.6                 |
| Shipping Weight (Kg)                  | 37.7                 |

## CONNECTIVITY (AUDIO/VIDEO) INPUT

|                  |   |
|------------------|---|
| HDMI             | 2 |
| DisplayPort      | 2 |
| Audio 3.5mm Jack | 1 |

## CONNECTIVITY (CONTROL/SERIAL DATA)

|           |   |
|-----------|---|
| RS232C IN | 1 |
| LAN Port  | 1 |
| USB       | 3 |

